

Code: TPC-BF5401-TB7

IP THERMAL IMAGING CAMERA **TPC-BF5401-TB7** - 1.4 Mpx, 7.5 mm DAHUA

The TPC-BF5401-TB7 Thermal Imaging Camera is a modern solution that allows to detect the presence of people, animals and vehicles regardless of prevailing vision conditions. The device is equipped with sensitive VOx microbolometer that allows to observe the objects in fog, smoke and in the absence of illumination. An additional advantage of the TPC series cameras is the ability to detect fire and send a signal to the alarm control panel when it occurs.

PoE powering possibility, compatible with the 802.3af standard makes the device more universal and easier to install.



| | |
|--------------------------------|--|
| Standard: | TCP/IP, CVBS |
| Sensor: | Uncooled VOx microbolometer |
| Matrix size: | 400 x 300 px |
| Pixel pitch: | 17 μm |
| Thermal sensitivity (NETD): | ≤ 40 mK @ F1.0 |
| Spectral range: | 8 μm ... 14 μm |
| Resolution: | 1280 x 1024 - 1.4 Mpx , 1280 x 960 - 960p , 1280 x 720 - 720p , 400 x 300 |
| Lens: | 7.5 mm |
| View angle: | 54 ° |
| Video output: | CVBS, PAL - 1 Vpp / 75 Ω, BNC |
| RS-485 interface: | ✓ |
| Memory card slot: | Micro SD memory cards up to 256GB support (possible local recording) |
| Image compression method: | H.265 / H.264M / H.264H / H.264B / MJPEG |
| Alarm inputs / outputs: | 2 / 2 |
| Audio: | <ul style="list-style-type: none"> • Audio input • Audio output |
| Temperature measurement: | <ul style="list-style-type: none"> • Spot • Line • Area max. 12 positions |
| Temperature measurement range: | <ul style="list-style-type: none"> • -20 °C ... 150 °C, • 0 °C ... +550 °C |





DATA SHEET

| | |
|--------------------------------|---|
| Main stream frame rate: | 25 fps @ 1280 x 1024 |
| Network interface: | 10/100 Base-T (RJ-45) |
| Network protocols: | HTTP, HTTPS, TCP/IP, ARP, RTSP, RTP, UDP, RTCP, SMTP, FTP, DHCP, DNS, DDNS, PPPoE IPv4/IPv6, SNMP, QoS, UPnP, NTP |
| WEB Server: | Built-in |
| Max. number of on-line users: | 20 |
| ONVIF: | ✓ |
| Mobile phones support: | Port 37777 • Android: Free application DMSS • iOS (iPhone): Free application DMSS |
| Default IP address: | 192.168.1.108 |
| Default admin user / password: | admin / - The administrator password should be set at the first start |
| Web browser access ports: | 80, 37777 |
| PC client access ports: | 37777 |
| Mobile client access ports: | 37777 |
| Port ONVIF: | 80 |
| RTSP URL: | rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream |
| Main features: | <ul style="list-style-type: none">• DDE (Digital Detail Enhancement) - for high dynamic images, it automatically adjusts the contrast of the image to the temperature parameters. The DDE function is the ideal tool for quick and accurate testing of electrical installations. Thanks to it the image is much more detailed and sharpened• 2D-DNR, 3D-DNR - Digital Noise Reduction• ROI - improve the quality of selected parts of image• AGC - Automatic Gain Control• EIS - Electronic Image Stabilization• Mirror - Mirror image• D-ZOOM - Digital Zoom : 19 x• IVS analysis : crossing the line (tripwire), intrusion, object detection (people, vehicle), fire detection |
| Power supply: | <ul style="list-style-type: none">• 12 V DC / 1.2 A,• PoE (802.3af),• ePoE |
| Power consumption: | max. 13 W |
| Housing: | Compact - Metal |
| Color: | White |
| Operation temp: | -40 °C ... 70 °C |
| "Index of Protection": | IP67 |
| Weight: | 1.4 kg |
| Dimensions: | 291 x 104 x 97 mm |
| Supported languages: | English |



DATA SHEET

| | |
|-----------------------|----------------|
| Manufacturer / Brand: | DAHUA |
| Guarantee: | 3 years |

