

Code: APTI-AI203CA3-28W

## IP CAMERA **APTI-AI203CA3-28W** - 1080p 2.8 mm

IP camera with efficient H.264 / H.265 image compression algorithm for clear and smooth video streaming at maximal resolution of 1080p.

Camera bracket allows to adjust the camera to any direction, and power cables are hidden inside the bracket. The range of IR illumination according to the manufacturer data, depends on outer conditions (visibility - air transparency, environment, wall colors ie. scene reflectance).

PoE powering possibility, compatible with the 802.3af standard makes the device more universal and easier to install.

The camera has extensive functions of intelligent image analysis.



Standard:	TCP/IP
Matrix size:	2.1 Mpx
Sensor:	1/2.9 " Progressive Scan CMOS
Resolution:	1920 x 1080 - 1080p , 1280 x 720 - 720p
Lens:	2.8 mm
View angle:	<ul style="list-style-type: none"> <li>• 91 ° (manufacturer data)</li> <li>• 97 ° (our tests result)</li> </ul>
Range of IR illumination:	25 m
Image compression method:	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Main stream frame rate:	25 fps @ 1080p
Network interface:	10/100 Base-T (RJ-45)
Memory card slot:	—
Alarm inputs / outputs:	—
Audio:	<ul style="list-style-type: none"> <li>• Microphone built-in,</li> <li>• Audio transmission via network</li> </ul>
Network protocols:	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, SMTP, UDP



# DATA SHEET

WEB Server:	Built-in
Max. number of on-line users:	10
ONVIF:	19.12
RS-485 interface:	—
Mobile phones support:	Port no.: 80 or access by a cloud (P2P) <ul style="list-style-type: none"><li>• Android: Free application <a href="#">BitVision</a></li><li>• iOS (iPhone): Free application <a href="#">BitVision</a></li></ul>
Default IP address:	192.168.1.168
Default admin user / password:	admin / admin The administrator password should be set at the first start
Web browser access ports:	80
PC client access ports:	80
Mobile client access ports:	80
Port ONVIF:	80
RTSP URL:	<ul style="list-style-type: none"><li>• rtsp://user:password@ip_address:80/0 - Main stream</li><li>• rtsp://user:password@ip_address:80/1 - Sub stream</li></ul>
Main features:	<ul style="list-style-type: none"><li>• Intelligent image analysis : intrusion, motion detection based on human detection</li><li>• D-WDR - Wide Dynamic Range</li><li>• 3D-DNR - Digital Noise Reduction</li><li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li><li>• Flicker Control - The technology eliminates the tiring eyes flickering image effect</li><li>• Mirror - Mirror image</li><li>• BLC - Back Light Compensation</li><li>• Possibility to change the resolution, quality and bit rate</li><li>• ICR - Movable InfraRed filter</li><li>• Privacy zones - max. 3</li><li>• Day/Night mode - configurable</li><li>• Sharpness - sharper image outlines</li></ul>
Power supply:	<ul style="list-style-type: none"><li>• PoE (802.3af),</li><li>• 12 V DC / 290 mA</li></ul>
Power consumption:	≤ 3.5 W
Housing:	Compact - Aluminum
Color:	White
"Index of Protection":	IP67
Operation temp:	-20 °C ... 60 °C
Weight:	0.43 kg
Dimensions:	170 x 73 x 73 mm
Supported languages:	Polish, English, Bulgarian Czech, French, Spanish, Dutch, German, Portuguese, Russian, Turkish, Italian
Manufacturer / Brand:	APTI
Guarantee:	2 years