

Code: VTO1301R-W

VIDEO DOORPHONE **VTO1301R-W** Wi-Fi DAHUA

The device works with video doorphones, and other DAHUA panels. Video Doorphone is mounted in a surface housing.

Attention! The doorphone has no controllable outputs.



Compatibility:	DAHUA
Sensor:	1/2.8 ", 2 Mpx CMOS
View angle:	110 °
Image compression method:	H.264 / H.265
IR illuminator:	✓
Resolution:	• Main stream : 1280 x 720, 800 x 480, 720 x 576, 352 x 288 • Sub stream : 1920 x 1080, 800 x 480, 720 x 576, 352 x 288, 320 x 240
proximity reader built-in:	—
Wireless transmission range:	The range limited only by the availability of the Wi-Fi network
Wi-Fi standard:	IEEE 802.11b / IEEE 802.11g / IEEE 802.11n
Network interface:	2.4 GHz Wi-Fi
The number of subscribers served:	1

Main features:	• It can only work with the mobile application, without the VTH monitor, • The function of the monitor can be a smartphone, tablet or VTH internal panel, • Micro SD memory cards up to 256GB support (possible local recording), • Bidirectional communication, • Microphone built-in, • Speakers built-in, • Echo suppression and reduction / digital noise reduction, • Tamper detection - opening the enclosure, • Day/Night mode (color/b&w/auto), • ICR - Movable InfraRed filter, • WDR - 120 dB - Wide Dynamic Range, • 2D-DNR, 3D-DNR - Digital Noise Reduction
Mobile phones support:	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS
Power supply:	12 V DC / 1 A
Power consumption:	• ≤ 5 W (operation) • ≤ 3.5 W (Standby mode)
Housing:	Plastic (PC + ABS)
Color:	Graphite + Black
"Index of Protection":	IP65
Operation temp:	-40 °C ... 55 °C
Weight:	• 0.16 kg (without cover) • 0.20 kg (with cover)
Dimensions:	• 141 x 51 x 27 mm (without cover) • 150 x 57 x 35 mm (with cover)
Supported languages:	English
Manufacturer / Brand:	DAHUA
Guarantee:	3 years