

Code: ETIGER-S3B-S

ALARM KIT **ETIGER-S3B-S**

The ETIGER-S3B-S alarm set is an ideal solution for people looking for a simple and reliable alarm system for home applications. Thanks to wireless communication between the system components and its simple and intuitive configuration by phone, SMS or via a mobile application, there is no need to call the installer to install the devices.

The set includes: eTiger-S3b Sim Secual wireless alarm control panel, two ES-D1A wireless motion detectors, two ES-D3C wireless reed switches, two ES-RC1N wireless keyfobs and two ES-T1A RFID keyfobs.



Number of supported wireless devices:	max. 60 pcs
Number of supported remote control keyfobs:	max. 10 pcs, In the kit : 2 pcs
The RFID cards/keyfobs support:	max. 50 pcs, In the kit : 2 pcs
Number of supported wireless sirens:	max. 50 pcs (not included)
PIR detectors included:	2 pcs, Wireless
Magnetic contact included:	2 pcs, Wireless
Enclosure included:	✓
Keyboard included:	✓
Expander included :	—
Wireless:	433 MHz
Operating range in open area:	max. 80 m
Zones:	50
Built-in modules:	GSM
Access from PC:	—
Mobile phones support:	<ul style="list-style-type: none"> • Operation via telephone call using tone dialing, • Remote control of the control panel via SMS, • Android: Free application eTIGER Home, • iOS (iPhone): Free application eTIGER Home

Main features:	<ul style="list-style-type: none"> • Bidirectional communication, • Configuration and full control over the system by phone (call, SMS or application), • LED indication, • Built-in alarm siren - 100 dB, • Alarm mute function
Power supply:	<ul style="list-style-type: none"> • 12 V DC / 1 A (power adapter included) • Built-in battery that maintains the control panel operation during a power failure : 2 x 3.7 V / 800 mAh
Housing:	Plastic
Color:	White
Operation temp:	-10 °C ... 55 °C
Weight:	0.32 kg
Dimensions:	187 x 130 x 26 mm

MAGNETIC CONTACT:

Detection:	Opening the door or window
Alarm signaling:	Signal to control panel
Frequency range:	433 MHz
Radio communication range (at open area):	max. 80 m
Alarm inputs:	—
Main features:	<ul style="list-style-type: none"> • Tamper protections • Low battery level alarm
Battery:	1 x LR3 (AAA) 1.5 V (included)
Operation temp:	-10 °C ... 55 °C
Weight:	<ul style="list-style-type: none"> • 0.034 kg - Transmitter • 0.012 kg - Magnet
Dimensions:	<ul style="list-style-type: none"> • 60 x 45 x 18 mm - Transmitter • 45 x 19 x 18 mm - Magnet

PIR DETECTOR:

Application:	Indoor
Sensor type:	Passive Infra Red (PIR)
Frequency range:	433 MHz
Radio communication range (at open area):	max. 80 m
Detection range / Detection angle:	8 m / 110 °
Sensitivity adjustment:	—
Pet immunity:	—
Digital temperature compensation:	—
Alarm output:	Wireless
Main features:	<ul style="list-style-type: none"> • Tamper protections - opening the cover • Low battery level alarm • LED indicator

Housing:	Plastic
Color:	White
Battery:	2 x LR6 (AA) 1.5 V (included)
Operation temp:	-10 °C ... 55 °C
Weight:	0.094 kg
Dimensions:	107 x 53 x 33 mm

REMOTE CONTROL:

Frequency band:	433 MHz
Radio communication range (at open area):	max. 80 m
Main features:	<ul style="list-style-type: none">• LED indication• Large, readable buttons : arm, disarm, arming only perimeter protection zones, SOS• Configuration is done using the mobile application• Alarm mute function
Battery:	CR2025 3 V (included)
Operation temp:	-10 °C ... 55 °C
Weight:	0.02 kg
Dimensions:	55 x 32 x 11 mm

General information:

Manufacturer / Brand:	eTIGER
Guarantee:	2 years

