

Code: TMS-5/6S

MULTISWITCH **TMS-5/6S** 5 INPUTS / 6 OUTPUTS TRIAX



Inputs:	• 1 x 47 MHz ... 694 MHz - Active / 5 MHz ... 862 MHz - Passive, • 4 x 950 MHz ... 2200 MHz
Outputs:	6 x 47 ... 2200 MHz
TV amplification (cable pre-correction):	0 dB
SAT amplification (cable pre-correction):	-2 ... 3 dB
Isolation:	• Interpolarized H/V : 30 dB • Between inputs SAT/TV : 30 dB • Outputs : 30 dB - SAT • Outputs : 25 dB - TV
Return loss:	TV input : > 10 dB SAT input : > 10 dB Outputs : > 10 dB
Maximal output level SAT:	100 dB μ V (-35dB IMD3)
Maximal output level TV:	90 dB μ V (-60dB IMD3)
Switching signals:	13 V / 18 V, 0 / 22 kHz, DiSEqC 1.0, DiSEqC 2.0
LNB power supply:	max. 1000 mA
Pre-amplifiers powering:	—
Power supply:	180 ... 264 V AC
Weight:	0.74 kg
Dimensions:	250 x 145 x 62 mm
Manufacturer / Brand:	TRIAX



DATA SHEET

Guarantee:

6 years