

Code: VTO6541H

VIDEO DOORPHONE **VTO6541H** DAHUA

[How many VTH monitors and VTO door stations can be connected to the Dahua intercom installation?](#)



Compatibility:	DAHUA
Sensor:	1/2.7 ", 2 Mpx CMOS
Resolution:	Main stream : 720p - 1280 x 720 , Sub stream : 1080p - 1920 x 1080
Lens:	4 mm, F1.6
View angle:	87 °
Display:	4.3 " IPS - 800 x 480 px
Image compression method:	H.264
LED illuminator:	✓
IR illuminator:	✓

Main features:	• WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • Day/night mode • ICR - Movable InfraRed filter • Noise and echo reduction • Motion Detection • Taking pictures • Records a short video message if there is no response to the doorbell button • 20 000 indexed users • proximity reader built-in - 13.56 MHz S50 - Memory of 10 000 RFID cards, • Fingerprint reader built-in - Memory of 10000 fingerprint patterns, • Face recognition - Memory of 10000 face templates, • Keyboard built-in - Touch control keys, • Cooperation with the SIP server • Bidirectional communication, • Microphone built-in, • Speakers built-in, • Tamper signaling, • Alarm inputs / outputs : 2 / 2, • Relay output - NO / NC, • Door contact and request button for exit inputs, • RS-485, • Wiegand, • Opening the door : PIN / RFID card / Fingerprint / face detection / Remote client • View information : How many VTH monitors and VTO door stations can be connected to the Dahua intercom installation?
Housing:	Plastic (PC + ABS)
"Index of Protection":	IP65 - after additional sealing the housing connection with the mounting surface, e.g. with silicone
Color:	Black + Silver
Power supply:	12 V DC / 2 A
Power consumption:	≤ 18 W
Operation temp:	-30 °C ... 60 °C
Weight:	0.91 kg
Dimensions:	389 x 146 x 45 mm
Supported languages:	English, Bulgarian, Czech, Finnish, Polish, Slovenian, Slovak, Hungarian
Manufacturer / Brand:	DAHUA
Guarantee:	3 years