

DATA SHEET

Code: INKLO-98520 EMERGENCY LIGHTING PLAFOND **INKLO-98520** Intelight

The INKLO-98520 emergency plafond is perfect for lighting social rooms, offices, corridors, anterooms, halls, staircases and other rooms. Aesthetic body and matt lampshade made of durable plastic make the luminaire perfect for many interiors, providing eyepleasing, even lighting. Thanks to the increased degree of protection (IP66) and mechanical strength class (IK10), the luminaire can be installed in places where there is a risk of lamp damage or where there is high dust and high humidity.

The lamp is equipped with a battery that allows it to maintain its operation for 2 hours after a power failure.



Rated voltage:	220 240 V, 50 Hz
Power connector:	Spring terminals
Power consumption:	max. 13 W
Energy class:	F
Luminous flux:	890 lm
Light color:	Neutral, 4000 K
CRI:	≥ 80
LED lifetime:	50000 h
Main features:	 Surface mount, Built-in battery supporting the operation of the lamp for 2 hours after a power failure Battery : NiCd 3.6 V / 2500 mAh
Housing:	Plastic (polycarbonate)
"Index of Protection":	IP66
Strength class:	IK10
Color:	White
Operation temp:	10 °C 50 °C
Weight:	1.2 kg
Dimensions:	Ø 297 x 95 mm
Manufacturer / Brand:	Intelight
Guarantee:	2 years



INKLO-98520