

DATA SHEET

Code: SWITCHBOX-T-PRO/BLEBOX

TRIPLE SMART SWITCH SWITCHBOX-T-PRO/BLEBOX Wi-Fi, 230 V AC

The Wi-Fi SWITCHBOX-T-PRO/BLEBOX electrical smart switch allows you to control the devices connected to it using a physical switch, a web browser, an external BleBox μ WiFi controller or the wBox mobile application. The device has a built-in keyboard with 3 buttons for direct control of connected devices. To work with full functionality, the device requires connection to a home Wi-Fi network. Controlling BleBox devices via the cloud requires additionally connecting the home network to the Internet and enabling the "Remote access" function in the device configuration.

Beyond direct control, the device has the ability to program the on and off schedule and linking to different system events. Voice control allows you to control the device via voice commands from Amazon Alexa or the Google Assistant (Internet access required).

Attention! The device can operate with monostable (momentary), bistable and stair switches. Depending on the switches used, the way of invoking the action for each device should be properly configured.



Application:	switching devices on/off
Rated voltage:	230 V AC
Maximal total load:	• 3 x 3680 W (resistance load) - AC, • 3 x 500 W (inductive or capacitive load) - AC, • 3 x 380 W - DC
Total maximal current:	3 x 16 A
Number of inputs:	3
Number of outputs:	3
Connector type:	screw terminals
Wireless:	Wi-Fi, 2.4 GHz - IEEE 802.11g
Mobile phones support:	The wBox free application on Android The wBox free application on iOS



DATA SHEET

Main features:	• Supports max. 3 devices, • Local control by physical button, • schedule, • timer, • sunrise and sunset mode, • remote access, • voice control, • Keyboard built-in - 3 Touch control keys, • Backlit, touch control panel • Omnidirectional antenna Wi-Fi 5 dB, • SMA-RP socket • µWiFi technology support
Housing:	Self-extinguishing , Surface-mounted (box)
"Index of Protection":	IP44
Color:	Gray / Black
Color: Operation temp:	Gray / Black -20 °C 50 °C
	· ·
Operation temp:	-20 °C 50 °C
Operation temp: Weight:	-20 °C 50 °C 0.42 kg • 129 x 96 x 57 mm - without antenna • 285 x 96 x 57 mm - with antenna, vertical