

Code: RB931-2ND

ACCESS POINT **RB931-2ND** hAP mini, 2.4 GHz 300 Mbps MIKROTIK

The RB931-2ND access point broadcasts the Wi-Fi 4 generation wireless network in the 2.4 GHz band. Main applications include Internet accesses in small and medium size businesses, SOHO, and homes.

In addition, thanks to its small sizes and ease of use, the device is a great travel companion, allowing you to avoid using the guest network if only the hotel room has a wired interface for connecting to the Internet.



Frequency range:	2.4 GHz
Antenna type:	Omnidirectional antenna , Dual-chain - embedded 1.5 dBi
Standards:	IEEE 802.11 b/g/n
Baud rates:	300 Mbps
LAN ports:	2 x 10 / 100 Mbps LAN 1 x 10 / 100 Mbps Uplink
LED indicators:	Power, User, 2 x Ethernet, WAN
Receiver sensitivity:	2.4 GHz : • 1M : -96 dBm • 11M : -89 dBm • 6M : -93 dBm • 54M : -74 dBm • MCS0 : -93 dBm • MCS7 : -71 dBm
DHCP server:	✓
Firmware update:	✓

Operating system:	MikroTik RouterOS
Management interface:	Web browser
Default IP address:	192.168.88.1
Operation modes:	• Access Point, • CPE, • P2P, • Repeater
Transmitter power:	max. 22 dBm
Power supply:	5 V DC / 1 A (power adapter included)
Power consumption:	max. 3.5 W
Main features:	• MDI/MDI-X auto detection feature - auto detecting the data transmission mode • Built-in 3-port switch • Dual-chain • Mode button • RESET button
Operation temp:	-20 °C ... 70 °C
Weight:	0.065 kg
Dimensions:	83 x 81 x 48 mm (with stand)
Manufacturer / Brand:	MikroTik
Guarantee:	2 years