

Code: DS-7732NXI-K4

## NVR **DS-7732NXI-K4** 32 CHANNELS ACUSENSE Hikvision

NVR equipped with advanced functions of intelligent image analysis.



|                                     |                                                                                                                                                                                                                                                                                                  |
|-------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Standard:                           | TCP/IP                                                                                                                                                                                                                                                                                           |
| Supported resolutions:              | max. 12 Mpx - 4000 x 3000 px                                                                                                                                                                                                                                                                     |
| Video outputs:                      | 1 pcs HDMI 4K<br>1 pcs VGA<br>There is a possibility to configure a SPOT function on one of the output                                                                                                                                                                                           |
| Audio support:                      | <ul style="list-style-type: none"> <li>• 32 Channels - Audio from cameras</li> <li>• Bi-directional audio streaming support</li> </ul>                                                                                                                                                           |
| Audio inputs:                       | 1 pcs CINCH                                                                                                                                                                                                                                                                                      |
| Audio outputs:                      | 1 pcs CINCH                                                                                                                                                                                                                                                                                      |
| Image compression method:           | H.265+ / H.265 / H.264+ / H.264                                                                                                                                                                                                                                                                  |
| Bitrate:                            | max. 256 Mbps                                                                                                                                                                                                                                                                                    |
| Supported hard drives:              | 4 x 10 TB SATA                                                                                                                                                                                                                                                                                   |
| Recording modes:                    | Manual, Sensor, Motion detection, Schedule                                                                                                                                                                                                                                                       |
| External storage devices backup:    | Backup to USB drive (pendrive, external drive)                                                                                                                                                                                                                                                   |
| Searching and playback the records: | Records searching: by time and events type. Records playback: forward, backward, fast, slow<br>Advanced searching (to the one second accuracy)<br>All channels synchronous playback, Smart Search function<br>Records playback from max. 16 channels in the same time<br>Smart Playback function |
| Network interface:                  | 2 x RJ-45 10/100/1000 Base-TX                                                                                                                                                                                                                                                                    |
| Network functions:                  | <ul style="list-style-type: none"> <li>• Live image view, Playback the records, Backup the records</li> <li>• max. 128 on-line users - iVMS-4200 application</li> </ul>                                                                                                                          |
| Network protocols:                  | TCP/IP, DHCP, IPv4, IPv6, DNS, DDNS, NTP, RTSP, SADP, SMTP, SNMP, NFS, iSCSI, ISUP, UPnP, HTTP, HTTPS                                                                                                                                                                                            |



# DATA SHEET

|                                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ONVIF:                           | ✓                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Default IP address:              | 192.168.1.64                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Default admin user / password:   | admin / -<br>The administrator password should be set at the first start                                                                                                                                                                                                                                                                                                                                                                                               |
| Mobile phones support:           | Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"><li>• Android: Free application <a href="#">Hik-Connect</a></li><li>• iOS: Free application <a href="#">Hik-Connect</a></li></ul>                                                                                                                                                                                                                                                          |
| Web browser access ports:        | 80, 8000                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| PC client access ports:          | 8000                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Mobile client access ports:      | 8000                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| RTSP URL:                        | <ul style="list-style-type: none"><li>• rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no01/ - Main stream</li><li>• rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no02/ - Sub stream</li></ul>                                                                                                                                                                                                                                   |
| USB:                             | <ul style="list-style-type: none"><li>• 2 pcs USB 2.0</li><li>• 1 pcs USB 3.0</li></ul>                                                                                                                                                                                                                                                                                                                                                                                |
| Serial ports:                    | <ul style="list-style-type: none"><li>• 2 pcs RS-485</li><li>• 1 pcs RS-232</li></ul>                                                                                                                                                                                                                                                                                                                                                                                  |
| Alarm inputs / outputs:          | 16 / 4                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| PTZ control:                     | <ul style="list-style-type: none"><li>• IP Speed Dome Cameras</li><li>• RS-485 - PELCO-D/P and others</li></ul>                                                                                                                                                                                                                                                                                                                                                        |
| Motion Detection:                | ✓                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Intelligent image analysis:      | ✓                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Main features:                   | <ul style="list-style-type: none"><li>• Smart motion detection (with recognizing people and vehicles)</li><li>• Filtering of false alarms based on the recognition of persons and vehicles</li><li>• face detection</li><li>• Comparison of faces with images from the database</li><li>• Support for up to 16 face databases, including 20 000 face images</li><li>• Smart search for a person based on a face photo</li><li>• NVR from the AcuSense series</li></ul> |
| Mouse support:                   | ✓                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| IR remote controller in the set: | ✓                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Switch PoE:                      | —                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Power supply:                    | 100 ... 240 V AC, 50 / 60 Hz                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Power consumption:               | ≤ 20 W (without HDD)                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Operation temp:                  | -10 °C ... 55 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Weight:                          | 4.05 kg                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Dimensions:                      | 445 x 400 x 75 mm, RACK 19", 1.5U                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Supported languages:             | Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Ukrainian, Hungarian, Italian                                                                                                                                                                                                   |
| Manufacturer / Brand:            | Hikvision                                                                                                                                                                                                                                                                                                                                                                                                                                                              |



## DATA SHEET

---

|            |                |
|------------|----------------|
| SAP Code:  | 303616147      |
| Guarantee: | <b>3 years</b> |