

Code: DS-3T1306P-SI/HS

SWITCH POE **DS-3T1306P-SI/HS** 4-PORT SFP Hikvision

Due to reliability and ensuring high quality of transmission, the DS-3T1306P-SI/HS 10/100 Mb/s 4-port PoE desktop type switch is perfect solution for expanding home or office network. 4 ports support the Power over Ethernet (PoE) function.

DS-3T1306P-SI/HS is designed to mount on the DIN 35 mm rail.



LAN ports:	• 4 x RJ45 10/100 Base-T (4 x PoE (802.3af/at)), • 1 x RJ45 10/100/1000 Base-T - Uplink, • 1 x SFP 1000 Base-X - Uplink
Transmission speed:	• 10 / 100 Mbps - 4 LAN & PoE ports, • 10 / 100 / 1000 Mbps - RJ45 (Uplink), • 1000 Mbps - SFP (Uplink)
Maximal output power:	30 W / port PoE
Maximal total power:	60 W
MAC addresses table:	2k
Management:	✓
Default IP address:	192.168.1.64
Default admin user / password:	admin / -
Operation modes:	• Extend - 1 ... 4 ports : 300 m, 10 Mbps @ UTP cat. 5e, 6 • Port Isolation - 1 ... 4 ports • Watchdog PoE - 1 ... 4 ports
LED diodes:	Power, Link/Act, PoE, PoE Max, G1, G2



DATA SHEET

Main features:	• View topology and network status • The device supports 8-pin power supply - wires : 1-2(-), 3-6(+), 4-5(+), 7-8(-) • Endspan mode support - wires : 1-2(-), 3-6(+) • Midspan mode support - wires : 4-5(+), 7-8(-) • Remote update of software • System logs • Data Flow Control • Watchdog function • Storm Control function • Port mirroring function • Port isolation • QoS : Queue scheduling: SP, WRR, SP+WRR • VLAN : 4094 groups • Spanning Tree STP/RSTP • Spanning Tree ERPS • SNMPv1/v2c • Compliance with the LLDP protocol • DHCP • Devices for mounting on a DIN, TS-35 rail • Industrial wide temperature design.
Certificates:	CE, RoHS, FCC, WEEE, REACH
Protections:	—
Housing:	Metal, Desktop, DIN rail (TS-35)
Power supply:	• 48 ... 57 V DC - 2 inputs • 48 V AC / 1.36 A (power adapter included)
Power consumption:	max. 65 W
Operation temp:	-30 °C ... 65 °C
Weight:	0.39 kg
Dimensions:	158 x 102 x 32 mm
Manufacturer / Brand:	Hikvision
SAP Code:	301802344
Guarantee:	3 years