

Code: RG-RAP6262(G)

ACCESS POINT **RG-RAP6262(G)** Wi-Fi 6 2.4 GHz, 5 GHz 574 Mbps + 1201 Mbps REYEE

The RG-RAP6262(G) access point broadcasts 2 separate wireless networks in the 5 GHz band with speed 1201 Mb/s and in the 2.4 GHz band with speed 574 Mb/s. The Access Point is designed for outdoor use, ensuring good connectivity in extreme weather environments over longer distances.

Device allows to secure data transmission using the encryption protocols: WPA-PSK/WPA2-PSK/WPA-WPA2-PSK.

The product meets the IP68 tightness class.



Frequency range:	2.4 GHz, 5 GHz
Antenna type:	2x2 MU-MIMO, 2.4 GHz - 3 dBi / 5 GHz - 4 dBi, Integrated - 4 x Omnidirectional antenna
Standards:	IEEE 802.11 a/b/g/n/ac/ax
Baud rates:	2.4 GHz : max. 574 Mbps + 5 GHz : max. 1201 Mbps
Protections:	WPA-PSK, WPA2-PSK, WPA/WPA2-PSK
LAN ports:	2 x 10/100/1000 Mbps
Mobile phones support:	Android: Free application Ruijie Reyee iOS (iPhone): Free application Ruijie Reyee
Management interface:	Web browser, Ruijie Cloud
Default IP address:	10.44.77.254
Transmitter power:	≤ 26 dBm @ 2.4 GHz ≤ 25 dBm @ 5 GHz
Housing:	Outdoor, plastic (Weatherproof)
Overvoltage protection:	4 kV lightning
Power supply PoE:	✓
Power supply:	• PoE (802.3at) • 12 V / 1.5 A (power adapter not included)
Power consumption:	≤ 18 W
Operation temp:	-30 °C ... 65 °C
Permissible relative humidity:	0 % ... 100 %
Certificates:	CE, RoHS



DATA SHEET

Main features:	<ul style="list-style-type: none">• Access Point is managed through the web and the cloud (Ruijie Rejee application)• Mobile phones support• Number of users : 256 (max)• Multi-SSID (max. 8)• Enable/Disable Wireless Radio• WMM (Wi-Fi Multimedia)• Transmit power control• Support for Rejee Mesh technology• Beamforming (TxBF) - technology that allows to create a beam of radio waves in order to improve the quality of connection with client devices located further away from the signal source• Load balance• Rate limit• Wireless Network Schedule• Wireless transmission statistics• Access control• MAC addresses filtering• Wireless isolation between clients• SSID to VLAN mapping• Remote management• RESET button• LED indication• Power supply PoE• Easy to install on any wall or pole (mounting kit included)
"Index of Protection":	IP68
Weight:	1.6 kg
Dimensions:	380 x 230 x 195 mm (without mounting kit)
Pole diameters range:	Ø 70 ... Ø 140 mm
Manufacturer / Brand:	RUIJIE / REYEE
Guarantee:	3 years

