

Code: TC-C34UN SPEC:I8/A/E/Y/2.8-12MM/V4.2

IP CAMERA **TC-C34UN SPEC:I8/A/E/Y/2.8-12MM/V4.2** - 4 Mpx 2.8 ... 12 mm TIANDY

IP camera with efficient H.265 / H.264 image compression algorithm for clear and smooth video streaming at maximal resolution of 4 MPx.

The used motozoom lens with 2.8 ... 12 mm focal length allows to remote view angle adjustment.

PoE powering possibility, compatible with the 802.3af standard makes the device more universal and easier to install. The range of IR illumination according to the manufacturer data, depends on outer conditions (visibility - air transparency, environment, wall colors ie. scene reflectance).



Standard:	IP
Resolution:	2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p
Sensor:	1/2.9 " Progressive Scan CMOS
Lens:	2.8 ... 12 mm - Motozoom
View angle:	104 ° ... 30 °
Range of IR illumination:	80 m
RS-485 interface:	—
Memory card slot:	Micro SD card support up to 512GB
Image compression method:	S+265 / H.265 / H.264
Alarm inputs / outputs:	—
Audio:	• Microphone built-in • Audio transmission via network
Main stream frame rate:	25 fps @ 4 Mpx



DATA SHEET

Interface:	10/100 Base-TX (RJ-45)
WEB Server:	Built-in
Max. number of on-line users:	2
ONVIF:	✓
Mobile phones support:	Port no.: 3000 or access by a cloud (P2P) • Android: Free application EasyLive Plus • iOS (iPhone): Free application EasyLive Plus
Access from PC:	Port no.: 3000 or access by a cloud (P2P) - PC: Free application Easy7 Smart Client Express
Default IP address:	DHCP or 192.168.1.2
Default admin user / password:	admin / - The administrator password should be set at the first start
Web browser access ports:	80, 443, 3000, 3001, 3002, 23002
Mobile client access ports:	3000, 3001
PC client access ports:	3000, 3001
Intelligent image analysis:	• crossing the line (tripwire) • intrusion
Main features:	• WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • AGC - Automatic Gain Control • ROI - improve the quality of selected parts of image • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • Possibility to change the resolution, quality and bit rate • Day/night mode • Privacy zones • Motion Detection
Power supply:	• PoE (802.3af), • 12 V DC / 590 mA
Power consumption:	≤ 7 W
Housing:	Dome - Metal + Plastic
Color:	White
"Index of Protection":	IP67
Mechanical protection class:	—
Operation temp:	-30 °C ... 60 °C
Weight:	0.43 kg
Dimensions:	204 x 84 x 76 mm
Supported languages:	Polish, English, Albanian, Arabic, Spanish, Korean, French, Dutch, Hebrew, German, Portuguese, Russian, Thai, Turkish, Ukrainian, Vietnamese, Italian
Manufacturer / Brand:	TIANDY



DATA SHEET

Guarantee:

3 years