

DATA SHEET

Code: TC-R3232 SPEC:I/B/K/V3.1 NVR TC-R3232 SPEC:I/B/K/V3.1 32 CHANNELS TIANDY

The TC-R3232 SPEC:I/B/K/V3.1 digital recorder is a professional device applicable in surveillance systems. The H.265 / H.264 video compression standard using to record video data, allows to get the best possible quality of recorded image at minimal network transfer and disk storage capacity. The menu options layout has been designed for all users, even beginners can easy navigate and change parameters in DVR settings without any problem.



Standard:	IP
Supported resolutions:	max. 8 Mpx
Video outputs:	1 pcs HDMI 4K 1 pcs VGA
Audio support:	32 Channels - Audio from cameras
Audio inputs:	1 pcs
Audio outputs:	1 pcs
Image compression method:	S+265 / H.265 / S+264 / H.264
Supported hard drives:	2 x 10 TB SATA
Recording modes:	Manual, Motion Detection, Schedule
External storage devices backup:	Backup to USB drive (pendrive, external drive)
Searching and playback the records:	 Records searching: by time and events type. Records playback: forward, backward, fast, slow Advanced searching (to the one second accuracy) Playback max. 16 cameras in the same time
Network interface:	1 x RJ-45 - 10 / 100 / 1000 Mbps
Network functions:	Full support via network, Remote records copying, Web-Server built-in
ONVIF:	✓
Bitrate:	max. 160 Mbps
Default admin user / password:	admin / - The administrator password should be set at the first start
Default IP address:	192.168.1.3
RTSP URL:	rtsp://user:password@192.168.1.3:554/1/1 - Main stream rtsp://user:password@192.168.1.3:554/1/2 - Sub stream



DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl POL; 60-713 Poznań; Graniczna 10 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



DATA SHEET

Web browser access ports:	80, 443, 3000, 3001, 3002, 23002
PC client access ports:	3000, 3001
Mobile client access ports:	3000, 3001
Mobile phones support:	Port no.: 3000 or access by a cloud (P2P) • Android: Free application <u>EasyLive Plus</u> • iOS (iPhone): Free application <u>EasyLive Plus</u>
Access from PC:	Port no.: 3000 or access by a cloud (P2P) - PC: Free application <u>Easy7 Smart Client</u> <u>Express</u>
Alarm inputs / outputs:	4 / 1
Motion Detection:	*
Intelligent image analysis:	-
USB:	2 x USB 2.0
Mouse support:	✓
IR remote controller in the set:	-
Main features:	Support for Intelligent Image Analysis function, available in TIANDY cameras : • crossing the line (tripwire) • double crossing the line • heat map • people counting • abandoned/missing object • detection of loitering in a given area • running • parking detection • detection of people gathering • detection of persons on duty • signal loss indication • face detection
Power supply:	12 V DC / 3.3 A (power adapter included)
Weight:	1.62 kg
Dimensions:	340 x 283 x 48 mm
Supported languages:	Polish, English, Chinese, Spanish, Korean, Italian, Turkish, Russian, Thai, French, Dutch, Hebrew, Arabic, Vietnamese, German, Ukrainian, Portuguese, Albanian
Manufacturer / Brand:	TIANDY
Guarantee:	3 years

