

Code: VTS5A40B

GUARD STATION **VTS5A40B** DAHUA

The VTS5A40B main station is a device allowing for consistent management of a large video doorphone installation. This panel allows contact with any internal panel in the system, support for all door stations and control of the opening of individual gates.

The device has been designed for local access control centres for housing estates or other facilities with a similar number of users.



Compatibility:	The SIP Systems
Shield:	10 " TFT-LCD color matrix
Resolution:	1024 x 600
Main features:	<ul style="list-style-type: none"> • Microphone built-in, • Speakers built-in, • A handset with a microphone that can be used interchangeably with the hands-free mode, • The Hirose 4-pin connector for connecting an external microphone, • 1 x USB 2.0 + 1 x USB 3.0, • 1 x HDMI - Video output, max. 1024 x 600 px, • Bidirectional communication - Audio, • Smooth adjustment of monitor parameters: image brightness, ring tone volume and conversation volume, • IP Dahua cameras support, • Noise and echo reduction, • The ability of direct communication between two or more panels, • Micro SD memory cards up to 512GB support (possible local recording), • Port RS-485, • Network interface: LAN - 100/1000 Base-T, • Cooperation with the SIP server
Controlling:	One-touch action buttons + capacitive touch screen
Default administrator password:	The administrator password should be set at the first start
Default user password:	123456
Alarm inputs:	4 pcs
Relay outputs:	1 pcs NO



DATA SHEET

Power supply:	12 V DC / 4 A (power adapter included) ,
Color:	Graphite
Operation temp:	-10 °C ... 55 °C
Weight:	1.64 kg
Dimensions:	345 x 225 x 28 mm
Supported languages:	English
Manufacturer / Brand:	DAHUA
Guarantee:	3 years