

Code: AT-UPS1200-T-LI/LED

UPS **AT-UPS1200-T-LI/LED** 1200 VA EAST

The AT-UPS1200-T-LI/LED UPS has been equipped with a number of advanced technologies ensuring active monitoring of the power supply network.

The device works with power supply adapters having Active Power Factor Correction (APFC).



Nominal power:	720 W
Apparent Power:	1200 VA
Input voltage:	230 V AC \pm 25 %
Input frequency:	50 / 60 Hz (auto detection)
Output voltage:	230 V AC \pm 10 % (Approximated Sine Wave)
Output frequency:	50 / 60 Hz
Transfer time:	2 ... 7 ms (typical), max. 10 ms
Charging time (recover to 90% capacity):	8 hours
Battery:	2 pcs - 12V/7Ah
Estimated battery operation time:	<ul style="list-style-type: none"> • 41 minutes @ 100 W, • 17 minutes @ 200 W, • 10 minutes @ 300 W, • 6 minutes @ 400 W, • 5 minutes @ 500 W , • 3 minutes @ 600 W
Number of outputs:	3 pcs CEE 7/3 (Schuko)

Protections:	<ul style="list-style-type: none"> • Glass Fuse • Short-circuit protection • Output current limiter • Overvoltage protection • Output voltage filtering • DC filter to eliminate interferences
Operation state indication:	<ul style="list-style-type: none"> • LED diodes, • Sound signaling
Main features:	<ul style="list-style-type: none"> • Auto restart while AC is recovering • Automatic Voltage Regulator (AVR) • Compatible with power generators • COLD START: - Cold start of the power adapter • Remote management - UPSmart application • Built-in EMI, RFI filter • Configurable alarm
Application:	<ul style="list-style-type: none"> • Surveillance Systems • data storage centers • network, servers, workstations • Industrial Equipment
Housing type:	Tower
Operation temp. / Relative humidity:	0 °C ... 40 °C / 20 ... 90 %
Weight:	10.17 kg
Dimensions:	330 x 227 x 125 mm
Manufacturer / Brand:	EAST
Guarantee:	2 years