

Code: COVER-WINTER-3K

UPS **COVER-WINTER-3K** 3000 VA COVER

The COVER-WINTER-3K UPS has been equipped with a number of advanced technologies ensuring active monitoring of the power supply network. The device is mounted to RACK 19" cabinet.

The line-interactive power supplies analyse the voltage, frequency and phase shift angle on a current basis, and filter the voltage transmitted to the connected devices. When a mains failure is detected, the UPS immediately switches to autonomous operation mode and continues to power the equipment using the energy accumulated in internal batteries.



| | |
|--|---|
| Power adapter type: | Line-interactive |
| Nominal power: | 2700 W |
| Apparent Power: | 3000 VA |
| Input voltage: | 162 V ... 290 V AC |
| Input frequency: | 50 / 60 Hz |
| Output voltage: | 208 V / 220 V / 230 V / 240 V AC (Pure Sine Wave) |
| Power factor: | 0.9 |
| Output frequency: | 50 / 60 Hz (auto detection) \pm 1 Hz |
| Transfer time: | max. 6 ms |
| Voltage adjustment: | — |
| Frequency adjustment: | — |
| Charging time (recover to 90% capacity): | 8 hours |
| Battery: | 6 pcs |



DATA SHEET

| | |
|--------------------------------------|--|
| Estimated battery operation time: | <ul style="list-style-type: none">• 12 minutes @ 1350 W,• 7 minutes @ 2025 W,• 4 minutes @ 2700 W |
| Number of outputs: | 8 pcs IEC-320 C13 + 1 pcs IEC-320 C19 |
| Management software: | ViewPower |
| Protections: | <ul style="list-style-type: none">• Short-circuit• Overload• Overcharge protection• discharge protection• Output voltage filtering• EPO (Emergency power off) switch |
| Operation state indication: | <ul style="list-style-type: none">• LCD display: operation mode, battery charging level, in/out voltage level,• Sound signaling |
| Main features: | <ul style="list-style-type: none">• Auto restart while AC is recovering• Automatic bypass• The device has a rotating display• COLD START function for manual switch to the battery power supply• Battery charge and maintenance control• Port RS-232 - Access from PC• Remote management - ViewPower application (included)• Battery replacement during operation (Hot-swap)• Network card slot• Can be mounted in a Rack 19" cabinet |
| Application: | <ul style="list-style-type: none">• Surveillance Systems• data storage centers• network, servers, workstations• Industrial Equipment |
| Housing type: | Rack/Tower 2-in-1 Design |
| Operation temp. / Relative humidity: | 0 °C ... 40 °C / 0 ~ 95 % (non-condensing) |
| Weight: | 29.2 kg |
| Dimensions: | 438 x 630 x 88 mm ; RACK 19", 2U |
| Manufacturer / Brand: | COVER |
| Guarantee: | 2 years |