

DATA SHEET

Code: XS12UPW

ELECTRIC STRIKE **XS12UPW** Hartte BIRA

The Hartte electric strikes XS-series are narrow (only 16.2 mm width) and have a small dimensions enabling mounting in narrow profiles and door frames.

They are built symmetrically - fit perfectly to left and right doors of various types. Radius latch (it is not outstanding out of electric strike outline) and adjustment in the range of $3.5\,$ mm requires less punching, and making installation easier and quicker. The memory function allows to control the electric strike by applying a short voltage pulse, after the termination of it the electric strike is open until the first opening of the door.



Rated voltage:	10 14 V AC/DC
Current consumption:	480 mA @ 12 V AC 680 mA @ 12 V DC
Application:	right-side door / left-side door
Ratched lock:	Ability to release the lock permanently
Memory function:	✓
Reverse action:	-
Clearance adjustment:	3.5 mm
Allowable load of the door impacting the lock:	3000 N
Allowable uninterrupted operation time:	-
Main features:	$ \begin{array}{l} \bullet \mbox{ Symmetrical housing} \\ \bullet \mbox{ Narrow profile} : 16.2 \mbox{ mm,} \\ \bullet \mbox{ Operation mode} : NC \\ \bullet \mbox{ Resistance} : 17.6 \Omega \\ \bullet \mbox{ Number of opening cycles} : 200000 \\ \bullet \mbox{ Radial shape of the latch} \cdot \mbox{ when opening the latch is not going beyond the outline of electric strike} \\ \end{array} $



DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl POL; 60-713 Poznań; Graniczna 10 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



DATA SHEET

Weight:	0.136 kg
Dimensions:	16.2 x 28 x 67 mm
Manufacturer / Brand:	BIRA
Guarantee:	2 years