

Code: APTI-20PV2-36WP-ECO

IP CAMERA **APTI-20PV2-36WP-ECO** - 3.7 Mpx 3.6 mm

IP camera with efficient H.264 / H.265 image compression algorithm for clear and smooth video streaming at maximal resolution of 4 MPx.

The range of IR illumination according to the manufacturer data, depends on outer conditions (visibility - air transparency, environment, wall colors ie. scene reflectance).

PoE powering possibility, compatible with the 802.3af standard makes the device more universal and easier to install.

Attention! Camera for indoor use only.



Standard:	IP
Resolution:	2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p
Sensor:	1/3 " Progressive Scan CMOS
Lens:	3.6 mm
View angle:	73 ° (manufacturer data)
Range of IR illumination:	25 m
Image compression method:	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs:	—
Main stream frame rate:	25 fps @ 3 Mpx
Network interface:	10/100 Base-T (RJ-45)
WEB Server:	Built-in - port 80
Max. number of on-line users:	10



DATA SHEET

ONVIF:	19.12
Intelligent image analysis:	<ul style="list-style-type: none">• intrusion• motion detection based on human detection
Main features:	<ul style="list-style-type: none">• D-WDR - Wide Dynamic Range• 3D-DNR - Digital Noise Reduction• Anti-Flicker - The technology eliminates the tiring eyes flickering image effect• ICR - Movable InfraRed filter• Possibility to change the resolution, quality and bit rate• BLC - Back Light Compensation• HLC - High Light Compensation (spot)• Motion Detection• Privacy zones• Day/night mode• Auto White Balance• Mirror - Mirror image• Sharpness - sharper image outlines
Mobile phones support:	Port no.: 80 or access by a cloud (P2P) <ul style="list-style-type: none">• Android: Free application BitVision• iOS (iPhone): Free application BitVision
Default IP address:	192.168.1.168
Default admin user / password:	admin / - The administrator password should be set at the first start
Web browser access ports:	80
PC client access ports:	80
Mobile client access ports:	80
Port ONVIF:	80
RTSP URL:	rtsp://user:password@ip_address:80/0 - Main stream rtsp://user:password@ip_address:80/1 - Sub stream
Power supply:	<ul style="list-style-type: none">• PoE (802.3af),• 12 V DC / 310 mA
Power consumption:	≤ 3.7 W
Housing:	Dome - Plastic
Color:	White
"Index of Protection":	—
Mechanical protection class:	—
Operation temp:	-20 °C ... 60 °C
Weight:	0.2 kg
Dimensions:	Ø 110 x 88 mm
Supported languages:	Polish, English, French, Spanish, Portuguese, Russian, Ukrainian, Hungarian, Italian
Manufacturer / Brand:	APTI
Guarantee:	2 years