

Code: VTO2111D-P-S3

VIDEO DOORPHONE **VTO2111D-P-S3** DAHUA

The device works with video doorphones, and other DAHUA panels. Video Doorphone is mounted in a surface housing.



Compatibility:	DAHUA
Sensor:	1/2.8 ", 2 Mpx CMOS
View angle:	107 °
Image compression method:	H.265 / H.264
IR illuminator:	✓
Resolution:	<ul style="list-style-type: none"> • Main stream : 1280 x 720, 800 x 480, 720 x 576 • Sub stream : 1920 x 1080, 800 x 480, 720 x 576, 352 x 288, 320 x 240
proximity reader built-in:	Access control cards - 13.56 MHz S50, Memory of 10 000 RFID cards
The number of subscribers served:	1

Main features:	<ul style="list-style-type: none"> • It can only work with the mobile application, without the VTH monitor • The function of the monitor with the ability to open the door can be a smartphone, tablet or the VTH indoor panel • Motion Detection • D-WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • Bidirectional communication, • Microphone built-in, • Speakers built-in, • Tamper detection - opening the enclosure, • Door contact and request button for exit inputs
Mobile phones support:	Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application DMSS • iOS (iPhone): Free application DMSS
Power supply:	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 1000 mA
Power consumption:	<ul style="list-style-type: none"> • ≤ 1 W (Standby mode), • ≤ 5 W (operation)
Housing:	Plastic, Waterproof
Color:	Graphite
"Index of Protection":	IP65 - after additional sealing the housing connection with the mounting surface, e.g. with silicone
IK rating:	IK04
Operation temp:	-30 °C ... 60 °C
Weight:	0.16 kg
Dimensions:	135 x 71 x 35 mm
Supported languages:	Polish, English, Bulgarian, Czech, Finnish, Slovenian, Slovak, Hungarian
Manufacturer / Brand:	DAHUA
Guarantee:	3 years