

Code: RG-ES216GC-V2

Switch **RG-ES216GC-V2** 16-PORT REYEE

The device is widely used in computer networks in offices (SOHO) and Small-to-Medium Businesses (SMB).



| | |
|--------------------------------|--|
| LAN ports: | 16 x (RJ45) 10/100/1000 Mbps |
| Management: | ✓ |
| Transmission speed: | 10/100/1000 Mbps - Gigabit Ethernet |
| Switching capacity: | 32 Gb/s |
| Forwarding rate: | 23.81 Mpps |
| MAC addresses table: | 8k |
| Certificates: | CE, RoHS |
| Number of fan coolers: | — |
| Mobile phones support: | Android: Free application Ruijie Reyee iOS (iPhone): Free application Ruijie Reyee |
| Default IP address: | 10.44.77.200 |
| Main features: | <ul style="list-style-type: none"> • Switch is managed through the web and the cloud (Ruijie Reyee application) • VLAN support <ul style="list-style-type: none"> - Range : 1 ... 4094 - 16 (max), • Can be mounted in a Rack cabinet • DHCP client • DHCP snooping support • Port mirroring function • Loop Protection • IEEE802.3x Flow Control • MTBF (Mean Time Between Faults) > 200.000 h |
| Operation temp: | 0 °C ... 50 °C |
| Permissible relative humidity: | 10 % ... 90 % (non-condensing) |
| Protections: | Protection against lightning discharges : 4 kV |
| Power supply: | 100 V ... 240 AC |



DATA SHEET

| | |
|-----------------------|----------------------------------|
| Power consumption: | ≤ 12 W |
| Weight: | 1.8 kg |
| Dimensions: | 440 x 165 x 44 mm / RACK 19", 1U |
| Manufacturer / Brand: | RUIJIE / REYEE |
| Guarantee: | 3 years |

