

## DATA SHEET

Code: BNC-W/ZAC-RG-6/PCT

## COMPRESSION PLUG BNC-W/ZAC-RG-6/PCT

Professional compression connector manufactured by American PCT company.

The connector is equipped with a plastic bush, which during compression of the connector is tightly pressed against the sheath of the cable (by putting on cone brass case - the compression ring). The dimensions are so matched that after compression connector is crimped on the cable sheath with a force so large that break the connector from the cable is impossible and so small that it does not damage the structure of the cable.



Connector type:	BNC Straight plug
Attachment of connector elements:	Compression mounting
Shield fastening:	Compression mounting
Wire mounting:	Pressing
Application:	Coaxial cable
Cable diameter:	max. 6.8 mm
Impedance:	75 Ω
Material:	Brass (Nickel-platted)
Watertightness:	<b>→</b>
Example of application:	• RG6
Main features:	Wide frequency range to 2 GHz Watertightness of connector with cable connection Resistance to corrosion - made of non-ferrous metals and highest-quality dielectric Very low loss in the whole operating band Perfect matching to the transmission line within the whole operating band Properly compressed connection is highly resistant to break Many patent-pending solutions To crimp use the crimping tool ZAC/PCT / ZAC/TR-255
Weight:	0.017 kg
Dimensions:	Ø 15 mm x 37 mm
Guarantee:	2 years