

Code: VGA+AU/VGA+Y+2AU

## MULTIMEDIA CONVERTER **VGA+AU/VGA+Y+2AU**

Converter allows to connect the laptop or computer or other equipment with VGA output to TV-set via Video Component YPbPr input.



|                        |                                                                                                                                                                                                                                                                      |
|------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Input:                 | 1x VGA<br>1x Audio (Jack 3.5mm socket)                                                                                                                                                                                                                               |
| Output:                | 1x Component video (Y Pb Pr), 1x VGA (bypass), 2x Audio (loop-through socket Jack 3.5mm), Cinch (R/L)                                                                                                                                                                |
| Supported resolutions: | 640x480 @ 60/75 Hz<br>800x600 @ 60/75 Hz<br>1024x768 @ 60/75 Hz<br>1280x800 @ 60 Hz<br>1280x1024 @ 60 Hz<br>480p, 720p, 1080i<br>640x480 @ 60/75 Hz (480p)<br>800x600 @ 60/75 Hz (720p)<br>1024x768 @ 60/75 Hz (720P lub 1080i)<br>1280x800 @ 60 Hz (720P lub 1080i) |
| Power supply:          | 5 V DC / 1 A (power adapter included)                                                                                                                                                                                                                                |
| Power consumption:     | max. 5 W                                                                                                                                                                                                                                                             |
| Operation temp:        | -25 °C ... 50 °C                                                                                                                                                                                                                                                     |
| Weight:                | 0.270 kg                                                                                                                                                                                                                                                             |
| Dimensions:            | 129 x 105 x 35 mm                                                                                                                                                                                                                                                    |
| Guarantee:             | 2 years                                                                                                                                                                                                                                                              |