

Code: CDV70-2810

VANDALPROOF CAMERA **CDV70-2810** STANDARD: PAL, 700 TVL 2.8 ... 10 mm

Camera equipped with perfect very high resolution Sony sensor and Sony Effio Digital Image Processor. Very high resolution of the camera sensor ensures more detailed image than standard CCTV camera.

Due to above, this camera is perfect solution for surveillance systems requiring persons or vehicles recognition, for example at places like: buildings entrance, lobbies, lounges, etc. Camera dome cover is protected against falling by metal cable.

Housing construction allows to mount the camera to the ceiling and the wall (image is right oriented in both cases). Camera module is mounted inside the dome housing, which allows to rotate the camera on any axis.

Camera is according to IP65 Index of Protection norm.



| | |
|--------------------------|--|
| Standard: | PAL |
| Sensor: | 1/3 " Sony EXview HAD II CCD |
| Digital Image Processor: | DSP Sony Effio-E |
| Resolution: | 700 TVL |
| Lens: | 2.8 ... 10 mm |
| Min. illumination: | 0.001 Lux |
| View angle: | 82 ° ... 27 ° (manufacturer data) 70 ° ... 28 ° (our tests result) |
| Electronic shutter: | 1/50 s ... 1/100 000 s |
| Video output: | 1 Vpp / 75 Ω |
| S/N ratio: | 52 dB |
| Vandal-proof: | ✓ |
| Main features: | <ul style="list-style-type: none"> • 2-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • WDR - Wide Dynamic Range • Max. 4 privacy zones • Day/night mode - manual/auto • White Balance - ATW/Manual • Sharpness - sharper image outlines • Mirror - horizontal |
| Power supply: | 12 V DC / 130 mA |
| OSD menu: | ✓ |
| "Index of Protection": | IP65 |
| Housing: | Dome - Metal |





DATA SHEET

| | |
|--------------------------------|------------------|
| Color: | White |
| Permissible relative humidity: | max. 95 % |
| Operation temp: | -10 °C ... 50 °C |
| Weight: | 0.490 kg |
| Dimensions: | Ø 119 x 90 mm |
| Guarantee: | 2 years |