

Code: 3B2-88RWM

PAL VANDALPROOF CAMERA **3B2-88RWM** 3.5 ... 8 mm

Vandal-proof camera with metal housing integrated with bracket. The 3 Axis bracket allows also to mount the camera to the ceiling. It is equipped with IR illuminator, which is turned on by twilight sensor when illumination conditions are low.

It has been equipped with extended OSD menu with many useful functions. Sense-UP - digital increase sensor sensitivity, DNR - Digital Noise Reduction which ensures clear image without any noise even at poor light conditions, DWDR - Wide Dynamic Range and HLC - High Light Compensation, eg car headlights.

Camera connectors (BNC and power) can be hidden inside the camera housing, what protects them against damage. Additionally, camera dome cover is protected against falling by metal cable.

Camera is according to IP55 Index of Protection norm.



Standard:	PAL
Sensor:	1/3 " Sony Super HAD CCD
Resolution:	600 TVL
Lens:	3.5 ... 8 mm
View angle:	69 ° ... 33 ° (manufacturer data) 60 ° ... 33 ° (our tests result)
Range of IR illumination:	20 m
S/N ratio:	> 50 dB
Video output:	1 Vpp / 75 Ω
Power supply:	12 V / 210 mA
Main features:	<ul style="list-style-type: none"> • Sense-UP - increase the camera sensitivity x512 • WDR - Wide Dynamic Range • 2-DNR - Digital Noise Reduction • AGC BLC - configurable Back Light Compensation • HLC - High Light Compensation (spot) • Motion Detection - max. 4 zones • Privacy zones - max. 8 • Mirror - Horizontal mirror image • Sharpness - sharper image outlines
Vandal-proof:	✓
Permissible relative humidity:	max. 95 %
"Index of Protection":	IP55
Housing:	Dome - Metal
Color:	White
Operation temp:	-10 °C ... 50 °C



DATA SHEET

Weight:	1.1 kg
Dimensions:	Ø 135 x 150 x 185 mm
Guarantee:	2 years