

Code: LG-32WL30MS-B

MONITOR VGA, HDMI, AUDIO, RS-232C, LAN, REMOTE CONTROLLER **LG-32WL30MS-B 32 "**

CCTV monitor with solid metal housing. The LED matrix illumination technology allows to real colors reproduction, 40% lower current consumption and much lower failure rate compared to normal LCD monitors with CCFL illumination. This model is equipped with all kinds of inputs, what allows to display an image from any kind of signals using in CCTV systems.

Monitor is designed to the display of advertising spots from computer in public places such as waiting rooms, etc. Very interesting solution is placing the speakers of the back side of housing. It does not bother listening to the AUDIO from the recorder at the same time does not reduce the area of the monitor front panel.

The device is designed to continuous work in closed spaces.



Screen size:	32 "
Native resolution:	1920 x 1080 px
Aspect ratios:	16 : 9
Matrix type:	IPS
Matrix backlight:	In LED technology
Supported standards:	PAL/NTSC
Contrast:	1300 : 1
Brightness:	400 cd/m ²
View angle:	178 ° horizontal 178 ° vertical
Response time:	25 ms
Speakers built-in:	2 x 10 W
Signal connectors:	<ul style="list-style-type: none"> • 1x HDMI • 1x DVI • 1x VGA • 1x LAN • 1x RS-232C • 1x USB • Audio input: (Jack) • audio output: 2x Cinch L/R
Housing type:	Metal
Monitor mounting standard:	VESA 200



DATA SHEET

Power supply:	230 V AC
Power consumption:	max. 65 W (operation)
Monitor control:	OSD - by IR remote controller or monitor control keys
Main features:	<ul style="list-style-type: none">• 3D Noise Reduction• PIP and POP functions - picture in picture and two pictures side by side• Auto Picture Adjustment
Operation temp:	0 °C ... 40 °C
Weight:	8.06 kg
Dimensions:	739 x 442 x 35 mm
Supported languages:	English, Chinese, Czech, Danish, French, Greek, Spanish, Japanese, German, Portuguese, Russian, Italian
Guarantee:	2 years