

Code: CD65-2812

CAMERA **CD65-2812** STANDARD: PAL, 650 TVL 2.8 ... 12 mm

The CD65-2812 camera is equipped with very high resolution Sony sensor. Due to above, this camera is perfect solution for surveillance systems requiring persons or vehicles recognition, for example at places like: buildings entrance, lobbies, entry gates, lounges, etc. Housing construction allows to ceiling and wall mounting (the image is right oriented in both cases). OSD menu controller is placed on the cable. For indoor use.



| | |
|--------------------|---|
| Standard: | PAL |
| Sensor: | 1/3 " Sony CCD |
| Resolution: | 650 TVL |
| Lens: | 2.8 ... 12 mm |
| View angle: | 81 ° ... 23 ° (manufacturer data) 88 ° ... 32 ° (our tests result) |
| Min. illumination: | 0.001 Lux |
| Video output: | 1 Vpp / 75 Ω |
| S/N ratio: | > 52 dB |
| Main features: | <ul style="list-style-type: none"> • WDR - Wide Dynamic Range • BLC - configurable Back Light Compensation • DIS - Digital Image Stabilization • EZOOM - Digital Zoom off • Motion Detection • Configurable Privacy Zones • Auto Gain Control • Mirror - Mirror image • Day/Night mode (color/b&w/auto) • Sharpness - sharper image outlines • HLC - High Light Compensation (spot) • DNR - Digital Noise Reduction |
| OSD menu: | ✓ |
| Power supply: | 12 V / 90 mA |
| Housing: | Dome - Plastic |
| Color: | White |



DATA SHEET

| | |
|-----------------|--|
| Application: | The camera is designed for indoor use, due to the possibility of steam condensation. |
| Operation temp: | -10 °C ... 50 °C |
| Weight: | 0.27 kg |
| Dimensions: | Ø 128 x 91 mm |
| Guarantee: | 2 years |