

Code: BCS-DMIP3200AIR-V

IP VANDALPROOF CAMERA **BCS-DMIP3200AIR-V** - 1080p 2.8 ... 12 mm

IP camera equipped with very good high resolution sensor. Due to above, this camera is perfect solution for surveillance systems requiring persons or vehicles recognition, for example at places like: buildings entrance, lobbies, entry gates, lounges, etc. Wide range of field of view adjustment allows to optimal set the monitoring area.

Very easy operation by Internet Explorer browser allows the users to convenient and remote support, and also remote management of the camera. Included camera software enables management and integrated monitoring of many network cameras. Its using allows to create large surveillance system.

ICR - The movable IR filter allows to perfect colors reproduction in daylight and wide gray-scale with high sharpness of the image at night mode.

PoE powering possibility, compatible with the 802.3af standard makes the device more universal and easier to install.



Standard:	TCP/IP
Sensor:	1/3 " Progressive Scan Aptina CMOS
Digital Image Processor:	DSP AMBARELLA
Matrix size:	2.1 Mpx
Resolution:	1920 x 1080 - 1080p , 1280 x 720 - 720p , 704 x 576 - D1 , 352 x 288 - CIF
Lens:	2.8 ... 12 mm
View angle:	<ul style="list-style-type: none"> • 81 ° ... 23 ° (manufacturer data) • 91 ° ... 33 ° (our tests result)
S/N ratio:	> 50 dB
Range of IR illumination:	20 m
RS-485 interface:	—
Memory card slot:	—
Image compression method:	H.264 / MJPEG
Alarm inputs / outputs:	—
Audio:	—
Bitrate:	32 ... 8192 kbps - H.264 32 ... 12288 kbps - MJPEG





DATA SHEET

Main stream frame rate:	25 fps - 1080p 25 fps - 720p
Network interface:	10/100 Base-T (RJ-45)
Network protocols:	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour
WEB Server:	Built-in
Max. number of on-line users:	20
ONVIF:	2.0
Mobile phones support:	Available applications for mobile devices with systems: Symbian, Windows Mobile, Android, Blackberry
Main features:	<ul style="list-style-type: none">• ICR - Movable InfraRed filter• 3D-DNR - Digital Noise Reduction• D-WDR - Wide Dynamic Range• Motion Detection• Privacy zones• Possibility to change the resolution, quality and bit rate• Sharpness - sharper image outlines
Vandal-proof:	✓
Color:	White
Power supply:	<ul style="list-style-type: none">• PoE (802.3af),• 12 V DC / 180 mA
Housing:	Dome - Metal
Operation temp:	-20 °C ... 60 °C
"Index of Protection":	IP66
Weight:	0.41 kg
Dimensions:	Ø 122 x 89 mm
Supported languages:	English, Polish
Manufacturer / Brand:	BCS
Guarantee:	2 years