

Code: JA-162A

WIRELESS INDOOR SIREN **JA-162A** JABLOTRON

The JA-162A wireless indoor siren can operate as: indoor alarm siren, multi-melody door bell, sounder for entrance / exit delay beeps. The siren communicates with alarm control panel via JABLOTRON protocol, and is mains-powered directly from AC 230V outlet.

When the JA-162A is used as the internal siren of the system, it sounds when an intruder alarm has been triggered and confirms the actual presence of an intruder in the building (tamper signals from next detectors). It sends a tamper signal to the alarm control panel when it gets unplugged.



Support:	JABLOTRON 100
Power consumption:	1 W
Frequency band:	868.1 MHz JABLOTRON protocol
Radio communication range (at open area):	100 m
Sounds (melodies):	8 selectable for buttons and detectors
Sound pressure level:	90 dB
Triggering devices:	1 x Alarm control panel max. 8 detectors/controllers
Safety class:	II according to EN60950
Operation environment:	according to EN 60529, IEC 529
Operation temp:	-10 °C ... 40 °C
Weight:	0.115 kg
Dimensions:	64
Power supply:	220 V
Dimensions:	x 90



DATA SHEET

Power supply:	... 240 V AC
Dimensions:	x 83 mm
Power supply:	@ 50Hz
Manufacturer / Brand:	JABLOTRON
Guarantee:	2 years