

Code: ATLO-KRM-102

CODE LOCK **ATLO-KRM-102**

Indoor, autonomous code lock with RFID reader.
Autonomous operation of the device allows the user to:

- Open by using a card or PIN code.
- Remember stored cards or PIN codes.
- Signaling left the door open.
- Acoustic and optical signaling.

Administrator capabilities are following:

- Programming by using the keypad.
- Adding a new card by using the keypad.
- Adding a new card and entering a PIN code.
- Changing the PIN code of the user.
- Deleting the PIN code of the user.
- Setting the lock release time.
- Restoring the default settings.



Cards support:	Unique EM 125kHz
Reading distance of prox-keys:	3 ... 6 cm
Autonomous operation:	✓
Keyboard built-in:	✓
Communication:	Wiegand 26
Doorbell button:	—
Tamper output:	—
Power supply:	12 V DC ± 10%
Maximal current consumption:	25 mA (Standby mode) 60 mA (operation)
Relay contacts load:	1 A / 12 V

Main features:	<ul style="list-style-type: none">• Number of relay outputs : 1,• 2000 indexed users,• Identification: Card and/or PIN• Blue backlight of the keys• Support for door contact and exit button• Electric strikes and electromagnetic locks support• Reversing bolt support• Tamper protection (detection of removing from mounting surface and enclosure opening)• Alarm output• NO/NC output• Possible connection of the external ATLO-R series reader (read in/out door control)
Operation temp:	-45 °C ... 60 °C
Permissible relative humidity:	10 ... 90 % (non-condensing)
"Index of Protection":	IP40
Housing:	Plastic (ABS)
Color:	Black
Weight:	0.09 kg
Dimensions:	82 x 92 x 21 mm
Manufacturer / Brand:	ATLO
Guarantee:	3 years