

Code: MOD/SIG-400/DVB-T

MODULATOR DVB-T **MOD/SIG-400/DVB-T**

The MOD/SIG-400/DVB-T digital modulator allows to put the HD signal (from camera, terrestrial, satellite TV receiver, Blu-ray, DVD player, etc.) from HDMI input to RF OUT output as DVB-T (COFDM), Full HD 1080p standard in VHF/UHF bands.



Inputs:	1 pcs HDMI, Full HD 1080p , 1 pcs RF (F)
Encoding:	H.264 MP@L 3.0/3.1/4.0
Supported HDMI resolutions:	480i @ 59.94 / 60 fps 576i @ 50 fps 720p @ 50 / 59.94 / 60 fps 1080i @ 50 / 59.94 / 60 fps 1080p @ 59.94 / 60 fps
Output:	1 pcs RF (F)
Insertion loss WE-WY VHF/UHF:	10 ... 12 dB
RF output level adjustment:	80 ... 93 dBμV
RF output frequency (channels) range:	142.5 ... 858 MHz
Modulation type:	QPSK, 16-QAM, 64-QAM
Power supply:	12 V DC / 2 A (power adapter included)
Main features:	• Firmware upgrade via USB cable • Aspect ratios 4:3, 16:9 • MER > 31 dB
Weight:	0.41 kg
Dimensions:	173 x 122 x 53 mm
Guarantee:	2 years