

Code: PK1-12-PWC

TIME RELAY MODULE **PK1-12-PWC** DELTA

The PK1-12-PWC time relay has 8 operating modes. Operation of the device may depend on the power supply only or the signal at the S control input. The control input can react to rising or falling edge, high or low state depending on the setting of the H/L jumper. The device has 2 time ranges: 230 ms ... 60 s and 2 s ... 10 min.



Number of relay outputs:	1
Power supply:	10 ... 16 V DC
Current consumption:	35 mA (max)
Relay maximal load:	10 A (max) @ 30 V DC / 50 V AC (max)
Output:	1 x NO/NC
Main features:	• Time settings range 1. Range : 0.23 s ... 60 s , 2. Range : 2 s ... 10 minutes • LED indication • Glass Fuse 10 A
Operation modes:	• Voltage switch-on delay • Voltage switch-off delay • Cycler - alternately switching on and off • Switch-off delay without the possibility of extension • Switch-off delay with the possibility of extension • Generation of extension pulse edge triggered • Bistable operation controlled by the S control input • Cycler with adjustable pulse filling
Operation temp:	-10 °C ... 40 °C
Weight:	0.092 kg
Dimensions:	120 x 91 x 36 mm
Manufacturer / Brand:	DELTA



DATA SHEET

Guarantee:

3 years