

Code: DH-HAC-HDW1100RP-VF

AHD, HD-CVI, HD-TVI, PAL VANDALPROOF CAMERA **DH-HAC-HDW1100RP-VF** - 720p 2.7 ... 12 mm DAHUA

Megapixel camera with 1/3" CMOS sensor and AHD / HD-CVI / HD-TVI / PAL.

The AHD / HD-CVI / HD-TVI interface allows to transmission of analog video signal via coaxial cable in 720p resolution. It enables the transmission of HD resolution images for even 500 m distance with keeping the low costs of the installation. During transmission there are no delays and is maintained the original, high quality image.

In the case of video transmission using a twisted pair cable and matching transformers (balun), be aware of the possibility of signal reflections and interfering signals.

Attention! The camera default setting is HD-CVI standard. To change the camera standard you need use the PFM820 controller, available separately. To change the standard, in which the camera is operating, the PFM820 controller is required.



Standard:	AHD, HD-CVI, HD-TVI, PAL
Sensor:	1/3 " Progressive Scan CMOS
Matrix size:	1.0 Mpx
Resolution:	1280 x 720 - 720p
IR illuminator support:	ICR - Movable InfraRed filter
Video output:	AHD / HD-CVI / HD-TVI / PAL - 1 Vpp / 75 Ω
OSD menu:	OSD menu available via recorder
Lens:	2.7 ... 12 mm, 2 Mpx
View angle:	<ul style="list-style-type: none"> • 89 ° ... 28 ° (manufacturer data) • 80 ° ... 26 ° (our tests result)
S/N ratio:	> 65 dB
Range of IR illumination:	30 m
IR illuminator power adjustment:	Automatic

Main features:	<ul style="list-style-type: none">• ICR - Movable InfraRed filter• 3D-DNR - Digital Noise Reduction• BLC - Back Light Compensation• AGC - Automatic Gain Control• Auto White Balance
Power supply:	12 V DC / 400 mA
Power consumption:	≤ 3 W
Housing:	Dome, Aluminum
Vandal-proof:	✓
Color:	White
"Index of Protection":	IP67
Operation temp:	-40 °C ... 60 °C
Weight:	0.55 kg
Dimensions:	Ø 119 x 97 mm
Manufacturer / Brand:	DAHUA
Guarantee:	3 years