

Code: LUMENA-1M1-12

IP PTZ CAMERA INDOOR **LUMENA-1M1-12** - 1.3 Mpx 2.8 mm

IP camera equipped with very good high resolution sensor. Due to above it is perfect solution for surveillance systems requiring persons or vehicles recognition. Included camera software enables management and integrated monitoring of many network cameras.



Standard:	TCP/IP
Sensor:	1/3 " OmniVision OV1035 CMOS
Digital Image Processor:	Hisilicon 3518C
Matrix size:	1.3 Mpx
Resolution:	1280 x 960 - 1.3 Mpx 1280 x 720 - 720p 640 x 480
Scanning system:	Progressive
Lens:	2.8 mm
View angle:	<ul style="list-style-type: none"> • 81 ° (manufacturer data) • 76 ° (our tests result)
Optical zoom:	—
Range of IR illumination:	15 m
S/N ratio:	≥ 50 dB
Video output:	—
Rotation speed (manual control):	0.1 °/s ... 12 °/s (horizontal) 0.1 °/s ... 10 °/s (vertical)
Preset rotation speed:	15 °/s

Horizontal rotation range:	355 °
Vertical rotation range:	0 ° ... 93 °
RS-485 interface:	—
Number of presets:	220
Horizontal scan:	✓
Route settings:	3
Image compression method:	H.264
Protections:	Overvoltage
Alarm inputs / outputs:	—
Network interface:	10/100 Base-T (RJ-45)
Network protocols:	TCP/IP, UDP, HTTP, DHCP, RTP/RTSP, DNS, DDNS, NTP, PPPOE, UPNP
Bitrate:	256 ... 10000 kbps
ONVIF:	✓
Mobile phones support:	Connection in cloud technology only • Android: Free application Cloudlens • iOS (iPhone): Free application Cloudlens
Main features:	<ul style="list-style-type: none"> • ICR - Movable InfraRed filter • DNR - Digital Noise Reduction • BLC - configurable Back Light Compensation • AGC - Automatic Gain Control • Auto White Balance • Day/Night mode (color/b&w/auto)
Power supply:	12 V DC / 0.83 A (power adapter not included)
Housing:	Dome, Plastic
Color:	Ivory
Operation temp:	-15 °C ... 60 °C
"Index of Protection":	IP40
Weight:	0.420 kg
Dimensions:	Ø 137 x 112 mm
Guarantee:	2 years