

Code: VFD-600/FR

UPS **VFD-600/FR** 600 VA

The VFD-600/FR UPS is a professional device used to maintain the operation of the components connected to it. The device has a small casing, economical design and automatic start in the absence of mains power.



Nominal power:	360 W
Apparent Power:	600 VA
Input voltage:	180 ... 270 V AC
Input frequency:	50 / 60 Hz (auto detection)
Output voltage:	230 V AC (Approximated Sine Wave)
Output frequency:	50 / 60 Hz \pm 1 %
Charging time (recover to 90% capacity):	to 8 hours
Estimated battery operation time:	<ul style="list-style-type: none"> • 7 minutes - 50% load • 0.5 minutes - 100% load
Battery:	12 V / 7 Ah
Number of outputs:	2 x "E" PL socket
Transfer time:	2 ... 6 ms
Operation state indication:	LEDs and buzzer
Protections:	<ul style="list-style-type: none"> • Overcharge protection • discharge protection • short-circuit protection • thermal protection
Main features:	<ul style="list-style-type: none"> • Excellent microprocessor control guarantees high reliability • Auto restart while AC is recovering • "Cold Start" function • Possibility to mount to the wall
Housing type:	Tower / Desktop



DATA SHEET

Dimensions:	228 x 206 x 83 mm
Weight:	2.91 kg
Manufacturer / Brand:	PowerWalker
Guarantee:	2 years