



User Manual

Code: DS-2AE4225TI-D(D)

AHD, HD-CVI, HD-TVI, CVBS SPEED DOME CAMERA OUTDOOR **DS-2AE4225TI-D(D)** - 1080p 4.8 ...
120 mm Hikvision

Warning!

Please read the user manual included in this work as it contains important information related with safety of installation and use of the device.

Only persons who read the user manual may use the device.

The user manual must be kept because it may be required in the future. The device is to be used exclusively for purposes specified in this user manual.

The device must be unpacked prior to starting-up. After removing the packaging make sure the device is in working order.

If the product has defects, it should not be used until it is repaired.

The product is intended for use at home and commercial use and may not be used for other than intended use.

The manufacturer is not liable for damages resulting from not adhering to the rules contained in the user manual, therefore, we recommend to follow the aforementioned safety rules for operation and maintenance of the device. In this way you will ensure yourself safety and avoid causing damage to the device.

The manufacturer and the supplier are not liable for losses or damages arising out of the product, including financial or intangible losses, loss of profits, income, data, pleasure from use of the product or other products related with it - indirect, incidental or consequential loss or damage. The above provisions apply whether the loss or damage concerns:

1. Deterioration of quality or the lack of operation of the products or products related with it due to damage as well as the lack of access to the product when it is undergoing repair, which results in stoppage the loss of user's time or a break in business activity;
2. Improper results of operation of the product or products related with it;
3. It applies to losses and damages according to any legal category, including negligence and other losses, termination of a contract, expressed or implied guarantee and strict liability (even if the manufacturer or the supplier was notified about the possibility of occurrence of such damages).

Safety measures:

Particular attention at designing was directed to quality standards of the device where ensuring safety of operation is the most important factor.

The device must be secured against contact with caustic, staining and viscous fluids.

The device was designed in such a way that it restarts operation when power supply is restored after a break.

Attention! We recommend using protections to further protect the device from possible overvoltages in installations. Surge protectors are effective protection against accidental pass to the device voltages higher than the rated. Damages caused by pass the voltages higher than specified in manual, are not under warranty.

Turn off the device before transporting it.

Prior to connecting the device to a power source check whether the supplied voltage is consistent with rated voltage specified in the user manual.

Proper product disposal:

A marking of a crossed out waste bin indicates that the product may not be disposed together with other household waste in the entire EU. To avoid possible damage to the natural environment of health due to uncontrolled waste disposal, therefore, it should be handed over for recycling, propagating in this way sustainable use of natural resources.

To return a worn-out product, use a collection and disposal system of this type of equipment or contact a seller from whom it was purchased. He will then be recycled in an environmentally-friendly way.

Megapixel camera with 1/2.8" CMOS sensor and AHD / HD-CVI / HD-TVI / PAL.
The AHD / HD-CVI / HD-TVI interface allows to transmission of analog video signal via coaxial cable in 1080p resolution. It enables the transmission of HD resolution images for even 500 m distance with keeping the low costs of the installation. During transmission there are no delays and is maintained the original, high quality image.



Standard:	AHD / HD-CVI / HD-TVI / CVBS
Sensor:	1/2.8 " Progressive Scan CMOS
Matrix size:	2.1 Mpx
Resolution:	1920 x 1080 - 1080p 960 x 576 - PAL
Range of IR illumination:	100 m
IR illuminator power adjustment:	Automatic
Lens:	4.8 ... 120 mm
View angle:	58 ° ... 2.2 ° (manufacturer data) 54 ° ... 3.2 ° (our tests result)
Optical zoom:	x 25
Digital zoom:	x 16
Rotation speed depending on ZOOM level:	✓
Horizontal rotation range:	360 ° continuous
Vertical rotation range:	-15 ° ... 90 °
Preset rotation speed:	80 ° (horizontal) 80 ° (vertical)



User Manual

Code: DS-2AE4225TI-D(D)

AHD, HD-CVI, HD-TVI, CVBS SPEED DOME CAMERA OUTDOOR **DS-2AE4225TI-D(D)** - 1080p 4.8 ...
120 mm Hikvision

Rotation speed (manual control):	0.1 °/s ... 80 °/s (horizontal) , 0.1 °/s ... 80 °/s (vertical)
PTZ control:	<ul style="list-style-type: none">• The ability to control via coaxial cable from recorder HIKVISION• Via interface RS-485
Protocols:	Pelco-D, Pelco-P
S/N ratio:	> 50 dB
Video output:	1 Vpp / 75 Ω, HD-TVI / CVBS
Number of presets:	256
Route settings:	10
Horizontal scan:	✓
Park action:	Call the set function (tour, scan, etc.) after specified dwell time
Main features:	<ul style="list-style-type: none">• 3D-DNR - Digital Noise Reduction• WDR - 120 dB - Wide Dynamic Range• EIS - Electronic Image Stabilization• IR illuminator optimization• Intelligent 3D Positioning System• ICR - Movable InfraRed filter• Privacy zones• BLC - Back Light Compensation• HLC - High Light Compensation (spot)• Auto White Balance
OSD menu:	✓
Vandal-proof:	—
"Index of Protection":	IP66
Power supply:	12 V DC
Power consumption:	≤ 20 W
Housing:	Speed Dome, Metal / Plastic
Color:	White / Black
Operation temp:	-30 °C ... 65 °C
Weight:	2.24 kg (without bracket) 2.97 kg (with bracket)
Dimensions:	Ø 165 x 295 mm (without bracket) 165 x 244 x 395
Supported languages:	English
Manufacturer / Brand:	Hikvision
SAP Code:	301205222
Guarantee:	3 years

Bottom view:



Internal view:






Bracket dimensions:



Camera connectors:



Dimensions (L x W x H): 0x0x0 mm Gross Weight: 0 kg