

Warning!

Please read the user manual included in this work as it contains important information related with safety of installation and use of the device.

Only persons who read the user manual may use the device.

The user manual must be kept because it may be required in the future. The device is to be used exclusively for purposes specified in this user manual.

The device must be unpacked prior to starting-up. After removing the packaging make sure the device is in working order. If the product has defects, it should not be used until it is repaired.

The product is intended for use at home and commercial use and may not be used for other than intended use.

The manufacturer is not liable for damages resulting from not adhering to the rules contained in the user manual, therefore, we recommend to follow the aforementioned safety rules for operation and maintenance of the device. In this way you will ensure yourself safety and avoid causing damage to the device.

The manufacturer and the supplier are not liable for losses or damages arising out of the product, including financial or intangible losses, loss of profits, income, data, pleasure from use of the product or other products related with it - indirect, incidental or consequential loss or damage. The above provisions apply whether the loss or damage concerns:

1. Deterioration of quality or the lack of operation of the products or products related with it due to damage as well as the lack of access to the product when it is undergoing repair, which results in stoppage the loss of user's time or a break in business activity; 2. Improper results of operation of the product or products related with it;

3. It applies to losses and damages according to any legal category, including negligence and other losses, termination of a contract, expressed or implied guarantee and strict liability (even if the manufacturer or the supplier was notified about the possibility of occurrence of such damages).

Safety measures:

Particular attention at designing was directed to quality standards of the device where ensuring safety of operation is the most important factor.

The device must be secured against contact with caustic, staining and viscous fluids.

The device was designed in such a way that it restarts operation when power supply is restored after a break.

Attention! We recommend using protections to further protect the device from possible overvoltages in installations. Surge protectors are effective protection against accidental pass to the device voltages higher than the rated. Damages caused by pass the voltages higher than specified in manual, are not under warranty.

Turn off the device before transporting it.

Prior to connecting the device to a power source check whether the supplied voltage is consistent with rated voltage specified in the user manual.

Proper product disposal:

A marking of a crossed out waste bin indicates that the product may not be disposed together with other household waste in the entire EU. To avoid possible damage to the natural environment of health due to uncontrolled waste disposal, therefore, it should be handed over for recycling, propagating in this way sustainable use of natural resources.

To return a worn-out product, use a collection and disposal system of this type of equipment or contact a seller from whom it was purchased. He will then be recycled in an environmentally-friendly way.





IP camera with efficient H.265 / H.264 image compression algorithm for clear and smooth video streaming at maximal resolution of $3840 \times 2160 - 4K$. Camera bracket allows to adjust the camera to any direction, and power cables are hidden inside the bracket. The range of IR illumination according to the manufacturer data, depends on outer conditions (visibility - air transparency, environment, wall colors ie. scene reflectance).

PoE powering possibility, compatible with the 802.3af standard makes the device more universal and easier to install.

Camera is according to IP66 Index of Protection norm.



Standard:	TCP/IP	
Sensor:	1/2.5 " SONY Starvis™ Back-illuminated CMOS	
Matrix size:	8 Mpx	
Resolution:	3840 x 2160 - 8.3 Mpx, 4K UHD , 3072 x 2048 - 6.3 Mpx , 2592 x 1944 - 5.0 Mpx , 2560 x 1920 - 4.9 Mpx , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p	
Lens:	4 mm	
View angle:	 81 ° (manufacturer data) 84 ° (our tests result) 	
S/N ratio:	> 50 dB	
Range of IR illumination:	20 m	
IR illuminator power adjustment:	Automatic	
Image compression method:	H.265+ / H.265 / H.264+ / H.264 / MJPEG	
Main stream frame rate:	20 fps @ 8 Mpx 30 fps @ 6 Mpx	
Network interface:	10/100 Base-T (RJ-45)	
Alarm inputs / outputs:	-	
Audio:	-	



DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl POL; 60-713 Poznań; Graniczna 10 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Network protocols:	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, SMTP
WEB Server:	Built-in - port 80
Max. number of on-line users:	10
ONVIF:	2.4
Memory card slot:	Micro SD memory cards up to 128GB support (possible local recording)
RS-485 interface:	-
Mobile phones support:	 Port no.: 80 or access by a cloud (P2P) Android: Free application <u>BitVision</u> iOS (iPhone): Free application <u>BitVision</u>
Default admin user / password:	admin / admin
Default IP address:	192.168.1.168
Web browser access ports:	80, 443
PC client access ports:	80
Mobile client access ports:	6000
Port ONVIF:	8999
RTSP URL:	rtsp://user:password@ip_address:554/0 - Main stream rtsp://user:password@ip_address:554/1 - Sub stream
Main features:	 2D-DNR, 3D-DNR - Digital Noise Reduction ICR - Movable InfraRed filter Flicker Control - The technology eliminates the tiring eyes flickering image effect Possibility to change the resolution, quality and bit rate D-WDR - Wide Dynamic Range BLC - Back Light Compensation F-DNR (Defog) - Reduction of image noise caused by precipitation Motion Detection Privacy zones Mirror - Mirror image Sharpness - sharper image outlines Day/Night mode - configurable
Power supply:	• PoE (802.3af), • 12 V DC / 280 mA
Power consumption:	≤ 3.4 W
Housing:	Compact, Aluminum
Color:	White
"Index of Protection":	IP66
Operation temp:	-20 °C 60 °C
Weight:	0.35 kg
Dimensions:	Ø 73 x 155 mm
Supported languages:	Polish, English, Bulgarian, Czech, French, Spanish, Dutch, German, Portuguese, Russian, Turkish, Italian
Manufacturer / Brand:	APTI





User Manual Code: APTI-83C2-4WP IP CAMERA APTI-83C2-4WP - 8.3 Mpx, 4K UHD 4 mm

2 years




Side view:



Bracket dimensions:







Memory card slot:



In the kit:



APTI-83C2-4WP





PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

