

SURVEILLANCE KIT **NK42W0-1T(WD)** Wi-Fi, 4 CHANNELS - 1080p 2.8 mm Hikvision

Warning!

Please read the user manual included in this work as it contains important information related with safety of installation and use of the device.

Only persons who read the user manual may use the device.

The user manual must be kept because it may be required in the future. The device is to be used exclusively for purposes specified in this user manual.

The device must be unpacked prior to starting-up. After removing the packaging make sure the device is in working order. If the product has defects, it should not be used until it is repaired.

The product is intended for use at home and commercial use and may not be used for other than intended use.

The manufacturer is not liable for damages resulting from not adhering to the rules contained in the user manual, therefore, we recommend to follow the aforementioned safety rules for operation and maintenance of the device. In this way you will ensure yourself safety and avoid causing damage to the device.

The manufacturer and the supplier are not liable for losses or damages arising out of the product, including financial or intangible losses, loss of profits, income, data, pleasure from use of the product or other products related with it - indirect, incidental or consequential loss or damage. The above provisions apply whether the loss or damage concerns:

- 1. Deterioration of quality or the lack of operation of the products or products related with it due to damage as well as the lack of access to the product when it is undergoing repair, which results in stoppage the loss of user's time or a break in business activity;
- 2. Improper results of operation of the product or products related with it;
- 3. It applies to losses and damages according to any legal category, including negligence and other losses, termination of a contract, expressed or implied guarantee and strict liability (even if the manufacturer or the supplier was notified about the possibility of occurrence of such damages).

Safety measures:

Particular attention at designing was directed to quality standards of the device where ensuring safety of operation is the most important factor.

The device must be secured against contact with caustic, staining and viscous fluids.

The device was designed in such a way that it restarts operation when power supply is restored after a break.

Attention! We recommend using protections to further protect the device from possible overvoltages in installations. Surge protectors are effective protection against accidental pass to the device voltages higher than the rated. Damages caused by pass the voltages higher than specified in manual, are not under warranty.

Turn off the device before transporting it.

Prior to connecting the device to a power source check whether the supplied voltage is consistent with rated voltage specified in the user manual.

Proper product disposal:

A marking of a crossed out waste bin indicates that the product may not be disposed together with other household waste in the entire EU. To avoid possible damage to the natural environment of health due to uncontrolled waste disposal, therefore, it should be handed over for recycling, propagating in this way sustainable use of natural resources.

To return a worn-out product, use a collection and disposal system of this type of equipment or contact a seller from whom it was purchased. He will then be recycled in an environmentally-friendly way.



Code: NK42W0-1T(WD) SURVEILLANCE KIT NK42W0-1T(WD) Wi-Fi, 4 CHANNELS - 1080p 2.8 mm Hikvision

The surveillance kit includes 4 cameras, Wi-Fi DVR with Western Digital 1TB hard disk, and 4 power adapters DC 12V / 1.5 A for independent camera power supply.

The H.264 video compression standard using to record video data, allows to get the best possible quality of recorded image at minimal network transfer and disk storage capacity. The menu options layout has been designed for all users, even beginners can easy navigate and change parameters in DVR settings without any problem.

 ${\bf Attention!}$ The DVR has installed the Western Digital 1TB hard disk.



Standard:	TCP/IP
Supported resolutions:	max. 4 Mpx - 2560 x 1440 px
Video outputs:	1 pcs HDMI 1 pcs VGA
Audio support:	4 Channels - Audio from cameras
Audio inputs:	-
Audio outputs:	1 pcs CINCH
Image compression method:	/ H.264+ / H.264 / MJPEG
Supported hard drives:	1 x 6 TB SATA, 1 TB - included
Recording modes:	Manual, Motion Detection, Schedule
Network protocols:	IPv6, UPnP, SADP, DHCP
External storage devices backup:	Backup to USB drive (pendrive, external drive)
Searching and playback the records:	Records searching: by time and events type. Records playback: forward, backward, fast, slow
Network functions:	Live image view, Playback the records, Backup the records - iVMS-4200 application Wi-Fi : $2.4\ \mathrm{GHz}$
Default IP address:	192.168.1.64
Default admin user / password:	admin / -





Code: NK42W0-1T(WD) SURVEILLANCE KIT **NK42W0-1T(WD)** Wi-Fi, 4 CHANNELS - 1080p 2.8 mm Hikvision

Web browser access ports:	80
PC client access ports:	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application
Mobile client access ports:	8000
RTSP URL:	• rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no01/ - Main stream • rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no02/ - Sub stream
Mobile phones support:	Port no.: 8000 or access by a cloud (P2P) • Android: Free application <u>iVMS-4500</u> or <u>Hik-Connect</u> • iOS (iPhone): Free application <u>iVMS-4500</u> or <u>Hik-Connect</u>
Alarm inputs / outputs:	-
PTZ control:	IP Speed Dome Cameras
Motion Detection:	~
USB:	2 pcs USB 2.0
Mouse support:	~
IR remote controller in the set:	-
Power supply:	12 V DC / 2 A
Weight:	1.4 kg
Dimensions:	260 x 248 x 48 mm
Supported languages:	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian
Camera:	
Standard:	TCP/IP
Sensor:	1/2.8 " Progressive Scan CMOS
Matrix size:	2.1 Mpx
Resolution:	1920 x 1080 - 1080p , 1280 x 720 - 720p
Operation modes:	Main and sub streams may be in any configuration Firmware V5.5.72 build: 190319 • Main stream: 1920 x 1080, 1280 x 720 • Sub stream: 640 x 480, 640 x 360, 320 x 240
Lens:	2.8 mm
View angle:	115 °
Compression:	/ H.264+ / H.264 / MJPEG
Range of IR illumination:	30 m
	-
Alarm inputs / outputs:	
Alarm inputs / outputs: Bitrate:	32 8192 kbps



Code: NK42W0-1T(WD) SURVEILLANCE KIT **NK42W0-1T(WD)** Wi-Fi, 4 CHANNELS - 1080p 2.8 mm Hikvision

Network interface:	• 10/100 Base-T (RJ-45)
	Wi-Fi - 2.4 GHz, IEEE 802.11 b/g/n TONUS JOANS LITTER LITTERS ETTS DIJOR DAYS DEPOS DETS DETSE D
Network protocols:	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP, QoS, Bonjour
Audio:	Microphone built-in
WEB Server:	Built-in, NVR compliance
Memory card slot:	-
Max. number of on-line users:	6
ONVIF:	✓
Mobile phones support:	Port no.: 8000 or access by a cloud (P2P) • Android: Free application <u>iVMS-4500</u> or <u>Hik-Connect</u> • iOS (iPhone): Free application <u>iVMS-4500</u> or <u>Hik-Connect</u>
Default IP address:	192.168.1.64
Default admin user / password:	admin / - The administrator password should be set at the first start
Web browser access ports:	80
PC client access ports:	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application
Mobile client access ports:	8000
Port ONVIF:	80
RTSP URL:	Main stream rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ - with authorization Sub stream rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ - with authorization
RS-485 interface:	-
Main features:	Wi-Fi module - IEEE 802.11 b/g/n, Antenna SMA socket D-WDR - Wide Dynamic Range 3D-DNR - Digital Noise Reduction Anti-Flicker - The technology eliminates the tiring eyes flickering image effect BLC - Back Light Compensation AGC - Automatic Gain Control ICR - Movable InfraRed filter Auto White Balance Privacy zones Motion Detection Mirror - Mirror image Sharpness - sharper image outlines
Power supply:	12 V DC / 420 mA
Power consumption:	≤ 5 W
Housing:	Compact, Metal + Plastic
Color:	White
"Index of Protection":	IP66
Operation temp:	-10 °C 55 °C



Code: NK42W0-1T(WD) SURVEILLANCE KIT **NK42W0-1T(WD)** Wi-Fi, 4 CHANNELS - 1080p 2.8 mm Hikvision

Weight:	0.27 kg	
Dimensions:	260 x 246 x 48 mm	
Supported languages:	English, Spanish, Portuguese, Russian	
General information:		
Cameras amount:	4 pcs	
Connecting cable:	_	
Power adapter:	• 4 pcs : 12 V DC / 1.5 A • 1 pcs : 12 V DC / 2 A	
Country of origin:	China	
Manufacturer / Brand:	Hikvision	
SAP Code:	311306147	
Guarantee:	3 years	

DVR:





Code: NK42W0-1T(WD)
SURVEILLANCE KIT **NK42W0-1T(WD)** Wi-Fi, 4 CHANNELS - 1080p 2.8 mm Hikvision





The DVR has installed the Western Digital 1TB hard disk:



CAMERA:



Code: NK42W0-1T(WD)
SURVEILLANCE KIT **NK42W0-1T(WD)** Wi-Fi, 4 CHANNELS - 1080p 2.8 mm Hikvision



Front view:





Code: NK42W0-1T(WD)
SURVEILLANCE KIT **NK42W0-1T(WD)** Wi-Fi, 4 CHANNELS - 1080p 2.8 mm Hikvision

Side view:



Antenna connector:



Mounting side view:



Code: NK42W0-1T(WD)
SURVEILLANCE KIT **NK42W0-1T(WD)** Wi-Fi, 4 CHANNELS - 1080p 2.8 mm Hikvision



In the kit:



Package:



Code: NK42W0-1T(WD)
SURVEILLANCE KIT **NK42W0-1T(WD)** Wi-Fi, 4 CHANNELS - 1080p 2.8 mm Hikvision



PACKAGE

Dimensions (L x W x H): 0x0x0 mm

Gross Weight: 0 kg