



# User Manual

Code: CF70-2812/4

PAL CAMERA **CF70-2812/4** 700 TVL 2.8 mm ... 12 mm

## Warning!

Please read the user manual included in this work as it contains important information related with safety of installation and use of the device.

Only persons who read the user manual may use the device.

The user manual must be kept because it may be required in the future. The device is to be used exclusively for purposes specified in this user manual.

The device must be unpacked prior to starting-up. After removing the packaging make sure the device is in working order.

If the product has defects, it should not be used until it is repaired.

The product is intended for use at home and commercial use and may not be used for other than intended use.

The manufacturer is not liable for damages resulting from not adhering to the rules contained in the user manual, therefore, we recommend to follow the aforementioned safety rules for operation and maintenance of the device. In this way you will ensure yourself safety and avoid causing damage to the device.

The manufacturer and the supplier are not liable for losses or damages arising out of the product, including financial or intangible losses, loss of profits, income, data, pleasure from use of the product or other products related with it - indirect, incidental or consequential loss or damage. The above provisions apply whether the loss or damage concerns:

1. Deterioration of quality or the lack of operation of the products or products related with it due to damage as well as the lack of access to the product when it is undergoing repair, which results in stoppage the loss of user's time or a break in business activity;
2. Improper results of operation of the product or products related with it;
3. It applies to losses and damages according to any legal category, including negligence and other losses, termination of a contract, expressed or implied guarantee and strict liability (even if the manufacturer or the supplier was notified about the possibility of occurrence of such damages).

### Safety measures:

Particular attention at designing was directed to quality standards of the device where ensuring safety of operation is the most important factor.

The device must be secured against contact with caustic, staining and viscous fluids.

The device was designed in such a way that it restarts operation when power supply is restored after a break.

**Attention! We recommend using protections to further protect the device from possible overvoltages in installations. Surge protectors are effective protection against accidental pass to the device voltages higher than the rated. Damages caused by pass the voltages higher than specified in manual, are not under warranty.**

Turn off the device before transporting it.

Prior to connecting the device to a power source check whether the supplied voltage is consistent with rated voltage specified in the user manual.

### Proper product disposal:

A marking of a crossed out waste bin indicates that the product may not be disposed together with other household waste in the entire EU. To avoid possible damage to the natural environment of health due to uncontrolled waste disposal, therefore, it should be handed over for recycling, propagating in this way sustainable use of natural resources.

To return a worn-out product, use a collection and disposal system of this type of equipment or contact a seller from whom it was purchased. He will then be recycled in an environmentally-friendly way.

Camera equipped with perfect very high resolution Sony sensor and Sony Effio Digital Image Processor. The built-in vari-focal lens allows to set very wide range of camera view angles.

Very high resolution of the camera sensor ensures more detailed image than standard CCTV camera. The high resolution sensor guarantees high detailed image, so this camera is perfect solution for surveillance systems requiring persons or vehicles recognition, for example at places like: buildings entrance, lobbies, gates, lounges, etc. OSD menu allows to set many useful functions and parameters.

The range of IR illumination according to the manufacturer data, depends on outer conditions (visibility - air transparency, environment, wall colors ie. scene reflectance).

OSD menu controller is placed on the cable. It allows to easily set or change the parameters and functions of the camera without move or unmount it.



Standard:	PAL
Sensor:	1/3 " Sony EXview HAD II CCD
Digital Image Processor:	DSP Sony Effio-E
Resolution:	700 TVL
Lens:	2.8 mm ... 12 mm
View angle:	81 ° ... 23 ° (manufacturer data) 81 ° ... 32 ° (our tests result)
Range of IR illumination:	40 m
Housing:	Metal
S/N ratio:	52 dB
Video output:	1 Vpp / 75 Ω
Power supply:	12 V / 190 mA
Main features:	<ul style="list-style-type: none"> <li>• WDR - Wide Dynamic Range</li> <li>• DNR - Digital Noise Reduction</li> <li>• Configurable Privacy Zones</li> <li>• Motion Detection</li> <li>• Sharpness - sharper image outlines - Mirror - Mirror image</li> <li>• Day/Night mode (color/b&amp;w/auto)</li> </ul>
OSD menu:	✓
Color:	Dark graphite
"Index of Protection":	IP66
Operation temp:	-10 °C ... 50 °C
Weight:	0.80 kg

Dimensions:	192 x 85 x 180 mm
Guarantee:	2 years

Front view:



Side view (the cable is hidden inside the bracket):



On the bottom of the camera there are two lens adjustment knobs (zoom, focus):



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------