

Code: APTI-H21V3-2812W

AHD, HD-CVI, HD-TVI, PAL VANDALPROOF CAMERA **APTI-H21V3-2812W** - 1080p  
2.8 ... 12 mm

Megapixel camera with 1/2.7" CMOS sensor and AHD / HD-CVI / HD-TVI / PAL.

The AHD / HD-CVI / HD-TVI interface allows to transmission of analog video signal via coaxial cable in 1080p resolution. It enables the transmission of HD resolution images for even 500 m distance with keeping the low costs of the installation. During transmission there are no delays and is maintained the original, high quality image.

Setting the camera in PAL mode allows to obtain an image in 960H resolution. The appropriate signal format selection is done by tilting and holding the joystick for 5 s without entering to the OSD menu. Changing the signal to the NTSC in the camera causes loss of image in connected AHD recorder.



|                                  |                                                                                                                                   |
|----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|
| Standard:                        | AHD, HD-CVI, HD-TVI, PAL                                                                                                          |
| Sensor:                          | 1/2.7 " Pixart CMOS                                                                                                               |
| Digital Image Processor:         | HTC1080                                                                                                                           |
| Matrix size:                     | 2.1 Mpx                                                                                                                           |
| Resolution:                      | 1920 x 1080 - 1080p, AHD-H, HD-CVI, HD-TVI ,<br>960 x 576 - 960H, PAL                                                             |
| Range of IR illumination:        | 30 m                                                                                                                              |
| IR illuminator power adjustment: | Automatic                                                                                                                         |
| Lens:                            | 2.8 ... 12 mm, 2 Mpx                                                                                                              |
| View angle:                      | <ul style="list-style-type: none"> <li>• 88 ° ... 25 ° (manufacturer data)</li> <li>• 98 ° ... 37 ° (our tests result)</li> </ul> |
| S/N ratio:                       | > 50 dB                                                                                                                           |
| Video output:                    | 1 Vpp 75 Ω, AHD / HD-CVI / HD-TVI / PAL - selectable by switch                                                                    |

|                        |                                                                                                                                                                                                                                                                               |
|------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Main features:         | <ul style="list-style-type: none"><li>• ICR - Movable InfraRed filter</li><li>• D-WDR - Wide Dynamic Range</li><li>• DNR - Digital Noise Reduction</li><li>• AGC - Automatic Gain Control</li><li>• Sharpness - sharper image outlines</li><li>• Auto White Balance</li></ul> |
| OSD menu:              | ✓                                                                                                                                                                                                                                                                             |
| Vandal-proof:          | ✓                                                                                                                                                                                                                                                                             |
| "Index of Protection": | IP66                                                                                                                                                                                                                                                                          |
| Power supply:          | 12 V DC / 390 mA                                                                                                                                                                                                                                                              |
| Power consumption:     | 4.7 W                                                                                                                                                                                                                                                                         |
| Housing:               | Dome - Metal                                                                                                                                                                                                                                                                  |
| Color:                 | White                                                                                                                                                                                                                                                                         |
| Operation temp:        | -20 °C ... 50 °C                                                                                                                                                                                                                                                              |
| Weight:                | 0.60 kg                                                                                                                                                                                                                                                                       |
| Dimensions:            | Ø 120 x 83 mm                                                                                                                                                                                                                                                                 |
| Supported languages:   | English, Chinese, Spanish, Italian                                                                                                                                                                                                                                            |
| Guarantee:             | 2 years                                                                                                                                                                                                                                                                       |