

Code: DH-IPC-HFW1320SP-W-0

IP CAMERA **DH-IPC-HFW1320SP-W-0** 360B Wi-Fi, - 3.0 Mpx 3.6 mm DAHUA

IP camera with efficient H.264 image compression algorithm for clear and smooth video streaming at maximal resolution of 2048 x 1536 (3.0 MPx).

The cameras of the Dahua Consumer series have been designed with special care to simplify the configuration and operation. In combination with the user friendly imou platform, the Dahua Consumer series devices allow anyone to create a simple and effective surveillance system.

The used Wi-Fi module allows to remote communication with camera for max. distance up to 50 m.

Attention! The Dahua Consumer cameras are dedicated to management only via the imou application (previous name Lechange). The IMOU series devices do not have a WEB interface. The Consumer series records the data only after motion detection (no continuous recording) - recording approx. 1 - 1.5 minutes depending on the duration of the movement in front of the camera. In order to obtain optimal performance of DAHUA Consumer series cameras, it is recommended to use DAHUA Micro SD memory cards.



Standard:	TCP/IP
Sensor:	1/3 " Progressive Scan CMOS
Matrix size:	3.0 Mpx
Scanning system:	Progressive
Resolution:	2304 x 1296 - 3.0 Mpx
Lens:	3.6 mm
View angle:	77 °
Range of IR illumination:	30 m
S/N ratio:	> 50 dB
Image compression method:	H.264
Alarm inputs / outputs:	—
Audio:	—
Bitrate:	32 kbps ... 8192 kbps - H.264
Main stream frame rate:	20 fps @ 2304 x 1296

Network interface:	10/100 Base-T (RJ-45) Wi-Fi IEEE 802.11 b/g/n
Network protocols:	TCP, DHCP
WEB Server:	—
Max. number of on-line users:	20
ONVIF:	—
Memory card slot:	Micro SD memory cards up to 128GB support (possible local recording)
Main features:	• Wi-Fi module - IEEE 802.11 b/g/n, Range : 50 m (open area) • Motion Detection
Mobile phones support:	Access by a cloud (P2P) • Android: Free application IMOU • iOS (iPhone): Free application IMOU
Default admin user / password:	admin / admin
Default IP address:	DHCP
Web browser access ports:	—
PC client access ports:	—
Mobile client access ports:	—
Port ONVIF:	—
RTSP URL:	—
Power supply:	12 V DC / 450 mA
Power consumption:	≤ 5.5 W
Housing:	Compact - Metal
Color:	White
"Index of Protection":	IP67
Operation temp:	-30 °C ... 50 °C
Weight:	0.428 kg
Dimensions:	144 x 68 x 67 mm
Supported languages:	—
Manufacturer / Brand:	DAHUA
Guarantee:	3 years