DATA SHEET

Code: PCS-260E

GSM COMMUNICATION MODULE **PCS-260E** PARADOX



Number of supported SIM cards:	2
Alarm inputs:	–
Alarm outputs:	–
Telephone numbers to reporting events:	max. 16
Event codes sending messages type:	SMS
Main features:	• 4G/3G/2G GSM network operation, • Reporting via GSM to the monitoring station, • Reporting via to the monitoring station, • SMS notification about an alarm or failure, • Sending the text messages (SMS) with event details, • The ability of remote arm/disarm the system by sending a text message (SMS), • Control panel communication supervision, • Installation to SERIAL connector of alarm control panel, • Possibility to connect the wire antenna, • Encrypted transmission - 128 bit, • Tamper protection (detection of removing from mounting surface and enclosure opening)
Transmitter power:	• 2 W @ 850 MHz, • 1 W @ 1800/1900 MHz
Power supply:	12 V DC

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

DATA SHEET

Current consumption:	300 mA (operation) 60 mA (Standby mode)
Operation temp:	-20 °C ... 50 °C
Dimensions:	207 x 74 x 21
Weight:	0.150 kg
Manufacturer / Brand:	PARADOX
Guarantee:	2 years

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60