

Code: LE-337204

SURFACE-MOUNTING DISTRIBUTION CABINET 96-MODULAR **LE-337204** XL³ S 160 LEGRAND

4-row 96-modular surface-mounting distribution electric cabinet.
NOTE: Doors and terminal blocks must be ordered separately.



Method of mounting:	Surface-mounted
Number of mounted modules:	24 x 4 rows
Spacing between TH 35 rails:	150 mm
Transparent door:	(not included)
Main features:	• Easily adjustable depth of the TH 35 chassis • Large capacity • Monobloc housing • Flexibility in the selection of terminal blocks • Possibility of connecting the housings vertically • Max. current : 160 A • Short-circuit current : 17 kA • Equipped with faceplates at full height
Equipment:	Faceplates : 1 x 4R
Material:	Steel
Color:	White
"Index of Protection":	• IP30 (without door) • IP40 (with door)



DATA SHEET

IK rating:	• IK04 (without door) • IK07 (with door)
Compliance with standards:	IEC/EN 61439-1, IEC/EN 61439-3, IEC 60695-2-1
Operation temp:	-5 °C ... 40 °C
Weight:	13.97 kg
Dimensions:	595 x 740 x 135 mm
Manufacturer / Brand:	LEGRAND
Guarantee:	2 years