

Code: LE-601942

SURFACE-MOUNTING HERMETIC DISTRIBUTION CABINET 24-MODULAR **LE-601942** RN65 LEGRAND

2-row 24-modular surface-mounting, hermetic distribution electric cabinet.



Method of mounting:	Surface-mounted
Number of mounted modules:	12 x 2 rows
Spacing between TH 35 rails:	150 mm
Transparent door:	✓
Main features:	• Weatherproof cabinet • Fully reversible door and cabinet • Removable chassis and faceplates • The TH 35 rail with 2-position mounting for modular products • Can be fitted with perforated plates and solid faceplates for mounting non-modular products • Lockable door handle, sealable cover and faceplate • Rated voltage : 400 V AC, 50 / 60 Hz • Max. current : 90 A • Short-circuit current : 10 kA • Equipped with terminal blocks and modules blanking plates
Equipment:	• Terminal blocks 1 x (16 x 1.5 ... 16 mm² + 1 x 6 ... 25 mm²) 2 x (8 x 1.5 ... 16 mm²) • Module blanking plates : 2 x 5 pcs



DATA SHEET

Material:	Self-extinguishing
Color:	Light gray
"Index of Protection":	IP65
IK rating:	IK09
Compliance with standards:	PN-EN 60439-3, IEC 60695-2-11, IEC 62262
Operation temp:	-25 °C ... 40 °C
Weight:	3.23 kg
Dimensions:	340 x 432 x 161 mm
Manufacturer / Brand:	LEGRAND
Guarantee:	2 years

