

Code: DS-2CE56D8T-IT3Z(2.8-12mm)

HD-TVI CAMERA **DS-2CE56D8T-IT3Z(2.8-12mm)** - 1080p Hikvision

Megapixel camera with Progressive Scan CMOS sensor and HD-TVI (High Definition Transport Video Interface).

The HD-TVI interface allows to transmission of analog video signal via coaxial cable at resolutions up to 1080p. It enables the transmission of HD resolution images for even 500 m distance with keeping the low costs of the installation. During transmission there are no delays and is maintained the original, high quality image.

Housing construction allows to mount the camera to the ceiling and the wall (image is right oriented in both cases).

Camera is according to IP67 Index of Protection norm.



Standard:	HD-TVI, PAL
Sensor:	Progressive Scan CMOS
Matrix size:	2.1 Mpx
Resolution:	1920 x 1080 - 1080p @ HD-TVI
Range of IR illumination:	40 m
IR illuminator power adjustment:	Automatic
Lens:	2.8 ... 12 mm - Motozoom
View angle:	• 103 ° ... 32 ° (manufacturer data) • 91 ° ... 32 ° (our tests result)
Video output:	1 x HD-TVI - BNC socket
Main features:	• Motozoom lens • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • Sense-UP - (Slow Shutter) - Increase the sensor sensitivity • EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners • ICR - Movable InfraRed filter • Privacy zones - max. 4 • Motion Detection - max. 4 zones • Mirror - Mirror image • Sharpness - sharper image outlines

OSD menu:	✓
Power supply:	12 V DC / 650 mA
Power consumption:	≤ 7.5 W
Housing:	Dome, Metal
Color:	White
"Index of Protection":	IP67
Operation temp:	-40 °C ... 60 °C
Weight:	0.58 kg
Dimensions:	134 x 124 x 111 mm
Supported languages:	English
Country of origin:	China
SAP Code:	300609632
Manufacturer / Brand:	Hikvision
Guarantee:	3 years