


## DATA SHEET

Code: VMT-193

## MONITOR 1xVIDEO, VGA, HDMI, AUDIO **VMT-193** 19.5 " VILUX



Monitor is perfect solution to work with PC, where there is a need to view the image from DVR in the same time. This model is equipped with all kinds of inputs, what allows to display an image from any kind of signals using in CCTV systems.

Interesting solution is placing the speakers of the back side of housing. It does not bother listening to the AUDIO from the recorder at the same time does not reduce the area of the monitor front panel.

The device is designed to continuous work in closed spaces.



Screen size:	19.5 "
Native resolution:	1920 x 1080 px
Aspect ratios:	16:9
Matrix type:	TFT-LCD color matrix
Matrix backlight:	In LED technology
Supported standards:	PAL/NTSC
Contrast:	500 : 1
Brightness:	250 cd/m <sup>2</sup>
Viewable angles:	160 ° horizontal 150 ° vertical
Response time:	5 ms
Speakers built-in:	2 x 2.5 W
Signal connectors:	Composite Video (BNC) sockets: 1x in, 1x out  1x VGA 1x HDMI Audio: 1x Jack (for VGA)





## DATA SHEET

Housing type:	Plastic
Monitor mounting standard:	VESA 75
Power supply:	12 V DC / 3 A (power adapter included)
Power consumption:	• max. 25 W (operation) • < 1 W (Standby mode)
MTBF (Mean Time Between Faults):	50000 h
Monitor control:	OSD - by monitor control keys
Main features:	<ul><li> 3D Comb Filter</li><li> 3D Noise Reduction</li><li> Auto Picture Adjustment</li></ul>
Operation temp:	-10 °C 50 °C
Weight:	2.42 kg (with stand)
Dimensions:	• 475 x 357 x 150 mm (with stand) • 475 x 298 x 35 mm (without stand)
Supported languages:	English, Chinese, French, Spanish, German, Polish, Portuguese, Russian, Italian
Manufacturer / Brand:	VILUX
Guarantee:	2 years