


## DATA SHEET

Code: RG-59+2X0.75/ZEL

## CCTV CABLE RG-59+2X0.75/ZEL

## CCTV specialized cable.

The cable complies with the CPR No. 305/2011 directive and meets the requirements of the PN-EN 50575 European standard which specifies requirements in fire conditions, test methods and rating of cables used as building material. The cable has a Declaration of Performance and a CE marking, which confirm its compliance with the guidelines of the CPR regulation.





In section:	100 m . Price for 1m when buying a whole roll
Coaxial cable:	RG59
Inner conductor:	Ø 0.59 mm - Cu wire
Dielectric:	Ø 3.7 mm PE full
Shield:	_
Braid:	Stranded wire Cu, Indoor coverage area : 90 %
Impedance:	75 Ω
Outer coating:	Ø 5.9 mm : PVC + gel
Cable attenuation at 100m section:	10.9 dB @ 100 MHz 15.2 dB @ 200 MHz 23.2 dB @ 450 MHz 32.6 dB @ 800 MHz 36.6 dB @ 1000 MHz
Electrical cable:	
Inner conductor:	2 x 0.75 mm <sup>2</sup> Stranded wire : Al + Cu
Power wires resistance:	4 Ω / 100 m
Outer coating:	Ø 5 mm
Guarantee:	2 years