

Code: BCS-DMIP1200IR-E-IV

## IP CAMERA **BCS-DMIP1200IR-E-IV** - 1080p 2.8 mm

IP camera with efficient H.264 / H.265 image compression algorithm for clear and smooth video streaming at maximal resolution of 1080p.

The range of IR illumination according to the manufacturer data, depends on outer conditions (visibility - air transparency, environment, wall colors ie. scene reflectance).

PoE powering possibility, compatible with the 802.3af standard makes the device more universal and easier to install.



|                           |                                                                                    |
|---------------------------|------------------------------------------------------------------------------------|
| Standard:                 | TCP/IP                                                                             |
| Sensor:                   | 1/3 " Progressive Scan CMOS                                                        |
| Scanning system:          | Progressive                                                                        |
| Matrix size:              | 2.1 Mpx                                                                            |
| Resolution:               | 1920 x 1080 - 1080p<br>1280 x 960 - 1.3 Mpx<br>1280 x 720 - 720p<br>704 x 576 - D1 |
| Lens:                     | 2.8 mm                                                                             |
| View angle:               | 110 °                                                                              |
| Range of IR illumination: | 30 m                                                                               |
| S/N ratio:                | > 50 dB                                                                            |
| Memory card slot:         | —                                                                                  |
| Image compression method: | H.265 / H.264 / MJPEG                                                              |
| Alarm inputs / outputs:   | —                                                                                  |
| Audio:                    | —                                                                                  |
| Bitrate:                  | 32 ... 10240 kbps - H.264                                                          |



# DATA SHEET

|                                |                                                                                                                                                                                                                                                                                                                                                                                       |
|--------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Main stream frame rate:        | 25 fps @ 1920 x 1080                                                                                                                                                                                                                                                                                                                                                                  |
| Network interface:             | 10/100 Base-T (RJ-45)                                                                                                                                                                                                                                                                                                                                                                 |
| Network protocols:             | IPv4/IPv6, HTTP, HTTPS, TCP, UDP, UPnP, ICMP, IGMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPoE, DDNS, FTP, IP Filter, Multicast, QoS, Bonjour                                                                                                                                                                                                                                             |
| WEB Server:                    | Built-in                                                                                                                                                                                                                                                                                                                                                                              |
| Max. number of on-line users:  | 20                                                                                                                                                                                                                                                                                                                                                                                    |
| ONVIF:                         | 2.42                                                                                                                                                                                                                                                                                                                                                                                  |
| Main features:                 | <ul style="list-style-type: none"><li>• 3D-DNR - Digital Noise Reduction</li><li>• D-WDR - Wide Dynamic Range</li><li>• BLC/HLC - Back Light / High Light Compensation</li><li>• Possibility to change the resolution, quality and bit rate</li><li>• Motion Detection</li><li>• Configurable Privacy Zones</li><li>• D-ZOOM - Digital Zoom</li><li>• Mirror - Mirror image</li></ul> |
| Mobile phones support:         | Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none"><li>• Android: Free application <a href="#">DMSS</a></li><li>• iOS (iPhone): Free application <a href="#">DMSS</a></li></ul>                                                                                                                                                                             |
| Default IP address:            | 192.168.1.108                                                                                                                                                                                                                                                                                                                                                                         |
| Default admin user / password: | admin / admin                                                                                                                                                                                                                                                                                                                                                                         |
| Web browser access ports:      | 80, 37777                                                                                                                                                                                                                                                                                                                                                                             |
| PC client access ports:        | 37777                                                                                                                                                                                                                                                                                                                                                                                 |
| Mobile client access ports:    | 37777                                                                                                                                                                                                                                                                                                                                                                                 |
| Port ONVIF:                    | 80                                                                                                                                                                                                                                                                                                                                                                                    |
| RTSP URL:                      | rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream<br>rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream                                                                                                                                                                                                       |
| Color:                         | White                                                                                                                                                                                                                                                                                                                                                                                 |
| Vandal-proof:                  | —                                                                                                                                                                                                                                                                                                                                                                                     |
| Power supply:                  | <ul style="list-style-type: none"><li>• PoE (802.3af),</li><li>• 12 V DC / 340 mA</li></ul>                                                                                                                                                                                                                                                                                           |
| Power consumption:             | ≤ 4.1 W                                                                                                                                                                                                                                                                                                                                                                               |
| Housing:                       | Dome - Metal                                                                                                                                                                                                                                                                                                                                                                          |
| "Index of Protection":         | IP66                                                                                                                                                                                                                                                                                                                                                                                  |
| Operation temp:                | -30 °C ... 60 °C                                                                                                                                                                                                                                                                                                                                                                      |
| Dimensions:                    | Ø 93 x 85 mm                                                                                                                                                                                                                                                                                                                                                                          |
| Weight:                        | 0.312 kg                                                                                                                                                                                                                                                                                                                                                                              |
| Supported languages:           | English, Polish                                                                                                                                                                                                                                                                                                                                                                       |
| Manufacturer / Brand:          | BCS                                                                                                                                                                                                                                                                                                                                                                                   |
| Guarantee:                     | <b>3 years</b>                                                                                                                                                                                                                                                                                                                                                                        |