

Code: VTO3211D-P2

VIDEO DOORPHONE **VT03211D-P2** DAHUA

The device works with video doorphones, and other DAHUA panels. Video Doorphone is mounted in a surface housing. The device generates a separate QR code for each room (for each VTH panel), which allows connection from the smartphone via the P2P network.
ATTENTION! The device does not support the Dahua analogue system.



Compatibility:	DAHUA
Sensor:	1/2.8 ", 2 Mpx CMOS
View angle:	140 °
Image compression method:	H.264
IR illuminator:	✓
proximity reader built-in:	Access control cards - 13.56 MHz S50
The number of subscribers served:	2
UTP category:	UTP cat. 5e
Main features:	• It can only work with the mobile application, without the VTH monitor • The function of the monitor with the ability to open the door can be a smartphone, tablet or the VTH indoor panel • Bidirectional communication, • Microphone built-in, • Speakers built-in, • Tamper detection - opening the enclosure, • Vandal-proof front panel, • Output for the additional lock release button

Power supply:	• PoE (802.3af), • 12 V DC / 580 mA
Power consumption:	≤ 7 W
Housing:	Aluminum - powder painted, Waterproof
Color:	Graphite
"Index of Protection":	IP65
Mechanical strength:	IK08
Operation temp:	-40 °C ... 60 °C
Weight:	0.47 kg
Dimensions:	182 x 101 x 31 mm
Supported languages:	English, Bulgarian, Czech, Finnish, Polish, Slovenian, Slovak, Hungarian
Manufacturer / Brand:	DAHUA
Guarantee:	3 years