

Code: BCS-TIP5401IR-V-IV

IP CAMERA **BCS-TIP5401IR-V-IV** - 4.0 Mpx, 2.7 ... 13.5 mm - MOTOZOOM

IP camera with efficient H.264 / H.265 image compression algorithm for clear and smooth video streaming at maximal resolution of 2688 x 1520 (4.0 MPx). Due to above it is perfect solution for surveillance systems requiring persons or vehicles recognition.

The used motozoom lens with 2.7 ... 12 mm focal length allows to remote view angle adjustment. PoE powering possibility, compatible with the 802.3af standard makes the device more universal and easier to install.

The range of IR illumination according to the manufacturer data, depends on outer conditions (visibility - air transparency, environment, wall colors ie. scene reflectance). Camera is according to IP66 Index of Protection norm.



Standard:	TCP/IP
Sensor:	1/3 " Progressive Scan CMOS
Matrix size:	4.0 Mpx
Resolution:	2688 x 1520 - 4.0 Mpx , 2560 x 1440 - 3.6 Mpx , 2304 x 1296 - 3.0 Mpx , 1920 x 1080 - 1080p , 1280 x 1024 - 1.4 Mpx , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p
Lens:	2.7 ... 13.5 mm - Motozoom
View angle:	• 104 ° ... 28 ° (manufacturer data) • 102 ° ... 27 ° (our tests result)
Compression:	H.265 / H.264 / MJPEG
S/N ratio:	> 50 dB
Range of IR illumination:	60 m
Alarm inputs / outputs:	—
Bitrate:	40 ... 10240 kbps - H.264



DATA SHEET

Main stream frame rate:	20 fps - 4.0 Mpx 25 fps - 3.7 Mpx
Network interface:	10/100 Base-T (RJ-45)
Network protocols:	HTTP, HTTPS, TCP, ARP, RTSP, RTP, UDP, SMTP, FTP, DHCP, DNS, DDNS, PPPoE, IPv4/IPv6, QoS, UPnP, NTP, Bonjour, IEEE 802.1x, Multicast, ICMP, IGMP, SNMP
Audio:	—
WEB Server:	Built-in, NVR compliance
Memory card slot:	Micro SD memory cards up to 128GB support (possible local recording)
Max. number of on-line users:	20
ONVIF:	16.12
Mobile phones support:	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS
Default admin user / password:	admin / admin
Default IP address:	192.168.1.108
Web browser access ports:	80, 37777
PC client access ports:	37777
Mobile client access ports:	37777
Port ONVIF:	80
RTSP URL:	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
RS-485 interface:	—
Main features:	• WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • Motion Detection • ICR - Movable InfraRed filter • Configurable Privacy Zones • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • AGC - Automatic Gain Control • Auto White Balance • Mirror - Mirror image • Sharpness - sharper image outlines • IVS analysis : crossing the line (tripwire)
Power supply:	• PoE (802.3af), • 12 V DC / 975 mA
Power consumption:	< 11.7 W
Operation temp:	-30 °C ... 60 °C
Housing:	Compact, Metal
Color:	White
"Index of Protection":	IP66



DATA SHEET

Supported languages:	English, Polish
Weight:	0.66 kg
Dimensions:	220 x 79 x 88 mm
Manufacturer / Brand:	BCS
Guarantee:	2 years